Form WWC-5 KSA 82a-1212 WATER WELL RECORD RANGE NUMBER 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION 1WE/W SE 27 Т 26 S R Sedgwick 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 3733 Estancia Ct. Wichita, Kansas MC CLELLAN ENTERPRUSES, INC WATER WELL OWNER: Board of Agriculture, Division of Water Resource 1108 W. 34th RR#,ST. ADDRESS,BOX #: ZIP CODE: 67204 CITY, STATE: Wichita, Kansas Application Number: 50 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: Ν 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/25/18 WELL'S STATIC WATER LEVEL hours of pumping @ gpm ft. after Well water was Pump test data: NE NW hours of pumping @ gpm ft after Est. Yield: Well water was Mile apm to 50 ft 12 and in. to Bore Hole Diameter WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES Was Water Well Disinfected? submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS ft. 5 Dia. 40 Dia. in to Blank casing diameter to ft.. to 12 Wall thickness or gauge No. Casing height above land surface: in., Weight: 2.35 lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1 Steel 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement 2. Brass 4. Galvanized 6. Concrete Tile SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 7. Torch cut 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 8. Saw cut 10. Other (specify) 2. Louvered shutter 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 40 50 ft., From ft. to ft. From to From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: 24 ft. to **50** ft., From ft. From ft. From From to ft.. to ft Other **GROUT MATERIALS:** 6 bentonite hole plug 2. Cement Grout 3. Bentonite 1. Neat cement 24 Grout Intervals: ft. ft.. ft. From From ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line West 10 ft. plus How many feet? Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From To From Τo topsoil 8 clay fine sand 8 20 20 50 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or plugged under my jurisdiction and

10/25/18 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year)

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

10/26/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb