Image Number
County:       SEDGWICK       NE ½ NW ½ NW ½ SW ½       28       T       26 s       R       1       E       W         2       WELL OWNER:       Last Name:       WALLACE       Frat:       SHERI       Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection):       If at owner's address, check here:         Address       8577 WEST CANDLEWOOD CT.       Address       Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection):       If at owner's address, check here:         Madress       8577 WEST CANDLEWOOD CT.       Address       Berthis Groundwater Encountered:       10.       If at owner's address, check here:       Image: Composition from nearest town or intersection):       If at owner's address, check here:         Madress       A DEPTH OF COMPLETED WELL:       .60 <th< td=""></th<>
2       WELL OWNER: Last Name:       WALLACE       First: SHERI       Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:         Address:       8577 WEST CANDLEWOOD CT.       direction from nearest town or intersection): If at owner's address, check here:         Address:       WICHITA       State: KS       ZIP: 67205         3       LOCATE WELL       4       DEPTH OF COMPLETED WELL:       .60.       ft.         N       V       Horizontal Datum:       UK       UK
Address:       8577 WEST CANDLEWOOD CT.         Address:       Civ:       WICHITA       State: KS       ZP: 67205         3 LOCATE WELL.       4 DEPTH OF COMPLETED WELL:       .60,, ft.       5 Latitude:
Address:       City:       WICHITA       State: KS       ZP. 67205         3       LOCATE WELL       4       DEPTH OF COMPLETED WELL:       .60,, ft.       5       Latitude:
3       LOCATE WELL WITH *X* N SECTION BOX: N       4       DEPTH OF COMPLETED WELL:69ft, Depth(s) Groundwate Encountered: 1)ft, 10mt, or 4] Dry Well N       5       Latitude:
WITH "X" IN SECTION BOX: N       4 DEPTH OF COWFLETED WELL:, MV ft. SECTION BOX: N       4 DEPTH OF COWFLETED WELL:, MV ft. SetMet MELL: STATL WATER LEVEL:, MV ft. SetMet MELL: STATL WATER LEVEL:, MV ft. Below land surface, measured on (mo-day-yr)/425/2019. Det Mell Astrace, measured mell Astrace, measured astrace, measure
SECTION BOX:       Depth(s) Groundwater Encountered:       1/.       m.       Longitude:       Longitude: <thlongitude:< th="">       Longitude:       Long</thlongitude:<>
W       WLL'S STATIC WATER LEVEL:
Image: Sector of the sector
W       H
w       ifter       hours pumping       gpm         well water was       ft.         after       hours pumping       gpm         bit       ft.       ft.         ft.       ft.       ft.         after       hours pumping       gpm         Bore Hole Diameter       ft.       ft.         ft.       ft.       ft.
Well water was       ft.         after.       hours pumping       gpm         stimuted Yield:       .22gpm         Bore Hole Diameter:       .10.5in. to       .60ft and         Y WELL WATER TO BE USED AS:
Allel:       Allel:       20gpm       gpin       6       Elevation:      ft.       Ground Level       □OC         S       Bore Hole Diameter:       .10.5in. to      ft.       GPS       Topographic Map         Image: Solution of the state of the
S       Bore Hole Diameter       10.5       in. to       60. ft and       Source:       Land Survey       GPS       Topographic Map         7       WELL WATER TO BE USED AS:       in. to       ft.       0 ther       0 ther       0 ther         1       Domestic:       5.       Public Water Supply: well ID       10.       0 if Field Water Supply: lease       11. Test Hole: well ID       12. Geothermal: how many bores?         2.       Irrigation       9. Environmental Remediation: well ID       2. Geothermal: how many bores?       12. Geothermal: how many bores?       13. Other (specify):         3.       Feedlot       Air Sparge       Soil Vapor Extraction       13. Other (specify):       a) Closed Loop       Surface Discharge       Inj. of Water         13.       Other CASING USED       Steel       PVC       Other       CASING JOINTS:       Glued       Clamed       Clamed       Threaded         Casing diameter       5       in. to       60. ft. Diameter       in. to       ft.       Diameter       in. to       ft.         YPE OF CASING USED       Steel       PVC       Other       Dother (Specify)       Casing height above land surface       17. in. to       ft.       ft.       ft.       ft.       ft.       ft.       ft.       ft.
inite
1. Domestic:       5. □ Public Water Supply: well ID       10. □ Oil Field Water Supply: lease         □ Household       6. □ Dewatering: how many wells?       11. Test Hole: well ID         □ Lawn & Garden       7. □ Aquifer Recharge: well ID       □ Cased □ Uncased □ Geotechnical         □ Livestock       8. □ Monitoring: well ID       □ Cased □ Uncased □ Geotechnical         2. □ Irrigation       9. Environmental Remediation: well ID       □ Closed Loop □ Horizontal □ Vertical         3. □ Feedlot       □ Air Sparge       □ Soil Vapor Extraction       b) Open Loop □ Surface Discharge □ Inj. of Water         4. □ Industrial       □ Recovery       □ Injection       13. □ Other (specify):
□ Household       6. □ Dewatering: how many wells?       11. Test Hole: well ID         □ Lawn & Garden       7. □ Aquifer Recharge: well ID       □ Cased □ Uncased □ Geotechnical         □ Livestock       8. □ Monitoring: well ID       □ Cased □ Uncased □ Geotechnical         3. □ Frequion       9. Environmental Remediation: well ID       □ Cased □ Uncased □ Geotechnical         3. □ Frequion       9. Environmental Remediation: well ID       □ Cosed Loop □ Horizontal □ Vertical         4. □ Industrial       □ Recovery □ Injection       13. □ Other (specify):         Was a chemical/bacteriological sample submitted to KDHE? □ Yes       ■ No       If yes, date sample was submitted:         Water well disinfected?       ■ Yes       ■ No       If yes, date sample was submitted:         Casing diameter       5. in. to       60. ft, Diameter       Ibs/ft.       Wall thickness or gauge No. SDR-26         TYPE OF SCREEN OR PERFORATION MATERIAL:       □ Steel       □ Fiberglass       ■ PVC       □ Other (Specify)       □ Other (Specify)         Brass       □ Galvanized Steel       □ Concrete tile       □ None used (open hole)       SCREEN OR PERFORATION OPENINGS ARE:         □ Continuous Slot       ■ Mill Slot       □ Gauze Wrapped       □ Torch Cut □ Drilled Holes       Other (Specify)       □ Concret ft, form         Continuous Slot       ■ Mill Slot
■ Lawn & Garden       7. □ Aquifer Recharge: well ID       □ Cased □ Uncased □ Geotechnical         □ Livestock       8. □ Monitoring: well ID       12. Geothermal: how many bores?         2. □ Irrigation       9. Environmental Remediation: well ID       a) Closed Loop □ Horizontal □ Vertical         3. □ Feedlot       □ Air Sparge       □ Soil Vapor Extraction       b) Open Loop □ Surface Discharge □ Inj. of Water         4. □ Industrial       □ Recovery       □ Injection       13. □ Other (specify):
□ Livestock       8. □ Monitoring: well ID       12. Geothermal: how many bores?         2. □ Irrigation       9. Environmental Remediation: well ID       a) Closed Loop □ Horizontal □ Vertical         3. □ Feedlot       □ Air Sparge       □ Soil Vapor Extraction       b) Open Loop □ Surface Discharge □ Inj. of Water         4. □ Industrial       □ Recovery       □ Injection       13. □ Other (specify):       a) Closed Loop □ Horizontal □ Vertical         Was a chemical/bacteriological sample submitted to KDHE?       □ Yes       ■ No       If yes, date sample was submitted:         Water well disinfected?       ■ Yes □ No       ■ PVC □ Other       CASING JOINTS:       ■ Glued □ Clamped □ Welded □ Threaded         Casing height above land surface
3. □ Feedlot       □ Air Sparge       □ Soil Vapor Extraction       b) Open Loop □ Surface Discharge □ Inj. of Water         4. □ Industrial       □ Recovery       □ Injection       13. □ Other (specify):         Was a chemical/bacteriological sample submitted to KDHE? □ Yes       ■ No       If yes, date sample was submitted:         Water well disinfected?       ■ Yes □ No       ■ PVC □ Other       CASING JOINTS: ■ Glued □ Clamped □ Welded □ Threaded         Casing diameter       .5       in to       .60       ft, Diameter
4. ☐ Industrial       ☐ Recovery       ☐ Injection       13. ☐ Other (specify):         Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes       No       If yes, date sample was submitted:         Water well disinfected?       Yes ☐ No       No       If yes, date sample was submitted:         8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No       If yes, date sample was submitted:         Water well disinfected? ■ Yes ☐ No       Yes ☐ No         8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other       CASING JOINTS: ■ Glued ☐ Clamped ☐ Welded ☐ Threaded         Casing diameter       5       in. to       60       ft, Diameter       in. to       in. to       ft.         Casing height above land surface       1/1       in. Weight       in. to       in. to       ft.         Casing height above land surface       1/1       in. Weight       ibs./ft.       Wall thickness or gauge No. SDR-26         TYPE OF SCREEN OR PERFORATION MATERIAL:       ☐       Stainless Steel ☐ Fiberglass       ■ PVC ☐ Other (Specify)         Brass       ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)       SCREEN OR PERFORATION OPENINGS ARE:         ☐ Continuous Slot       Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)
Water well disinfected?       Yes       No         8 TYPE OF CASING USED:       Steel       PVC       Other       CASING JOINTS:       Glued       Clamped       Welded       Threaded         Casing diameter       5       in. to       60       ft. Diameter       in. to       ft. Diameter       in. to       ft. Diameter       in. to       ft. Casing height above land surface       ft.       in. Weight       lbs./ft. Wall thickness or gauge No. SDR-26       ft.         Casing height above land surface       ///       in. Weight       lbs./ft.       Wall thickness or gauge No. SDR-26       ft.         TYPE OF SCREEN OR PERFORATION MATERIAL:
8 TYPE OF CASING USED:       □ Steel       ■ PVC       □ Other       CASING JOINTS:       ■ Glued       □ Clamped       □ Welded       □ Threaded         Casing diameter
Casing diameter       5       in. to       60       ft., Diameter       in. to       ft., Diameter       in. to       ft.         Casing height above land surface       14       in. Weight       lbs./ft.       Wall thickness or gauge No. SDR-26         TYPE OF SCREEN OR PERFORATION MATERIAL:       Steel       Steel       Fiberglass       PVC       Other (Specify)         Brass       Galvanized Steel       Concrete tile       None used (open hole)       Other (Specify)       SCREEN OR PERFORATION OPENINGS ARE:         Continuous Slot       Mill Slot       Gauze Wrapped       Torch Cut       Drilled Holes       Other (Specify)         Louvered Shutter       Key Punched       Wire Wrapped       Saw Cut       None (Open Hole)         SCREEN-PERFORATED INTERVALS:       From       45       ft. to       60       ft., From       ft. to       ft.         GRAVEL PACK INTERVALS:       From       32       ft. to       60       ft., From       ft. to       ft.         9 GROUT MATERIAL:       Neat cement       Cement grout       Bentonite       Other       Other       ft. to       ft.
Casing height above land surface
□ Steel       □ Stainless Steel       □ Fiberglass       ■ PVC       □ Other (Specify)         □ Brass       □ Galvanized Steel       □ Concrete tile       □ None used (open hole)         SCREEN OR PERFORATION OPENINGS ARE:       □ Continuous Slot       ■ Mill Slot       □ Gauze Wrapped       □ Torch Cut       □ Drilled Holes       □ Other (Specify)         □ Louvered Shutter       □ Key Punched       □ Wire Wrapped       □ Saw Cut       □ None (Open Hole)         SCREEN-PERFORATED INTERVALS:       From
□ Brass       □ Galvanized Steel       □ Concrete tile       □ None used (open hole)         SCREEN OR PERFORATION OPENINGS ARE:       □ Continuous Slot       ■ Mill Slot       □ Gauze Wrapped       □ Torch Cut       □ Drilled Holes       □ Other (Specify)         □ Louvered Shutter       □ Key Punched       □ Wire Wrapped       □ Saw Cut       □ None (Open Hole)         SCREEN-PERFORATED INTERVALS:       From
SCREEN OR PERFORATION OPENINGS ARE:         □ Continuous Slot       ■ Mill Slot       □ Gauze Wrapped       □ Torch Cut       □ Drilled Holes       □ Other (Specify)         □ Louvered Shutter       □ Key Punched       □ Wire Wrapped       □ Saw Cut       □ None (Open Hole)         SCREEN-PERFORATED INTERVALS:       From
Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)     SCREEN-PERFORATED INTERVALS: Fromft. toft. to
SCREEN-PERFORATED INTERVALS: From
GRAVEL PACK INTERVALS: From
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
Grout Intervals: From
Nearest source of possible contamination:         Septic Tank       Lateral Lines         Pit Privy       Livestock Pens         Insecticide Storage
Image: Septic Tank       Image: Lateral Lines       Image: Pit Privy       Image: Livestock Pens       Image: Image: Livestock Pens         Image: Seware Lines       Image: Cess Pool       Image: Seware Lagoon       Image: Fuel Storage       Image: Abandoned Water Well
■ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well
Other (Specify) Direction from well? NORTH Distance from well? .18
Direction from well?         NON IT         Distance from well?         Domestic           10 FROM         TO         LITHOLOGIC LOG         FROM         TO         LITHO. LOG (cont.) or PLUGGING INTERVALS
1 2 TOP SOIL
2 13 CLAY
13 32 GRAVEL
32 33 CLAY
34 39 FINE SAND
39 60 GRAVEL Notes:
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged
under my jurisdiction and was completed on (mo-day-year) 4/29/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 884
under the husiness name of WENINGER DRILLING LLC. Signature
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015