	WATER WEL	L RECORD F	orm WV	VC-5 K	SA 82a-12 ⁻	12		_	
1 LOCATION OF WATER WELL:	FRACTION					TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick		IW 1/4 NE	1/4	27	T 2	6 S	R 1W	/ E/W	
Distance and direction from nearest town or city	•	· ·							
5918 W. Driftwood Ct.	WI BL Building Grou	chita, Kansas							
	0 W. North Wind	-				Board of Agric	culture, Division of W	ater Resource	
	hita, Kansas	Stc #100	ZI	P CODE: 6	7205	Application Num	nber:		
	DEPTH OF COMPLET	ED WELL: 4		. 000	ELEVATION:				
WITH AN "X" IN SECTION BOX:	epth of groundwater End		ft.			ft.		ft.	
	/ELL'S STATIC WATER				RFACE MEASU		lav/vr: 8/12	/20	
		est data: Well wa		ב	ft. after		of pumping @	gpm	
		gpm Well wa			ft. after	hours	of pumping @	gpm	
∑ w E E	Bore Hole Diameter	12 in.	to 4	10 ft.	and	in.	to	ft.	
1 1 1	VELL WATER TO BE US					9. Dewaterii	ng 11. Injed	tion well	
	1. Domestic 3. Fee				nd garden only	ー 10. Monitorin	12. Other (Sp	ecify below)	
	2. Irrigation 4. Indu Was a chemical/bacteriolog	ustrial 6. Oil field w		YES	NO		w <u>hat</u> mo/day/yr w	as sample	
· · · · · · · · · · · · · · · · · · ·	ubmitte d		- -		Vater Well Disin	fected?	YES N	10	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. O	ther (Specify	below) CAS	SING JOINTS: (Glued	Threaded	
1. Steel 3. RPM (S	sk)		so SDI	R-26			Welded	Clamped	
2. PVC 4. ABS	6. Asbestos-Ce		iic		-				
Blank casing diameter 5	in. to 30	ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above land surface:	12 _{in.,}	Weight:	2.35 R	bs. / ft.	Wall th	ickness or gaug	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENIN		(3)				(,		
1. Continuous slot 3. Mill s		zed wrapped	7 To	rch cut	9. Drill	led holes	11. None (o	pen hole)	
		wrapped		w cut		er (specify)	•	. ,	
,	·	••				er (apecity)			
SCREEN - PERFORATION INTERVAL		30 ft. to		ft.,	From	ft.	to	ft.	
25475	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	1,0,	24 ft. to	•	ft.,	From	ft.	to	ft.	
	From	ft. to) 	ft.,	From	ft.	to	ft.	
—		. Cement Grout	3	3. Bentonite		Other bent	onite hole plu	_	
Grout Intervals: From	ft. to	ft., From	ft.	to	ft.,	From 4	ft. to	24 ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas						as well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							ecify below)		
3. Watertight sewer line 6. Seepa	age pit 9. Fee	ed yard	12. Fertilize	r storage					
Direction from well? West					How ma	any feet? 20 f	ft. plus		
From To	LITHOLOGIC L	OG	From	То		LITHOLO	GIC LOG		
0 3 topsoil			ļ	ļ <u></u>					
3 23 fine sand 23 40 medium sand			-						
23 40 Intention Said	<u> </u>	*******	 						
			↓			······································			
					· · · · · · · · · · · · · · · · · · ·				
			<u> </u>	 					
							-		
						'	W		
 			1						
7 0	Cardian This star "				or 3	nlugged	under my jurisdicti	on and	
7 Contractor's or Landowner's Certif				constructed	•		unuer my junisuich	on anu	
was completed on (mo/day/year) 8/12/2020 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/14/2020									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									