	WATER WEL	L RECORD	Form WV	VC-5 K	SA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION	~~~	1	TION NUMBER	1		NUMBER
Sedgwick		SW 1/4 SW	/ 1/4	27	T 26 S	R 1	W E/W
Distance and direction from nearest town or city 3827 N. Estancia Ct.		a, Kansas					
2 WATER WELL OWNER: MC CLELLAN ENTERPRISES INC.							
RR#.ST. ADDRESS,BOX #: 321 E. Dakota Ct.							
CITY, STATE: Kech	ni, Kansas		Z	P CODE: 6	7067 Applicat	tion Number:	
	DEPTH OF COMPLET	TED WELL:	50 ft.		ELEVATION:		
WITH AN "X" IN SECTION BOX: Dep	pth of groundwater En	ncountered:	ft		ft.		ft.
WE	ELL'S STATIC WATE	R LEVEL 15	FT. BELC	W LAND SU	IRFACE MEASURED OF		30/20
NWNE	•		vater was		ft. after	hours of pumping @	
W W E B	Est. Yield: lore Hole Diameter	gpm Well v	water was to	50 ft.	ft. after and	hours of pumping @ in. to	gpm ft.
	ELL WATER TO BE L	JSED AS:			9 De		jection well
	. Domestic 3. Fee	edlot 5. Public	water supply	7. Lawn a	and garden only	12. Other	(Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well ; If yes, what mo/day/yr was sample							
	Vas a chemical/bacteriolo ibmitted	ogical sample submitted	to Department?	YES Was V	NO ; ! Vater Well Disinfected?	YES	NO NO
5 TYPE OF CASING USED:		7 5%	9.0	ther (Specify		INTS: Glued	Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING SOLVES. Welded Clamped							
2. PVC 4. ABS	6. Asbestos-Ce	ement 8. Concrete	e tile SD	K-20			
Blank casing diameter 5	in. to 40	ft., Dia.	in.	to	ft., Dia.	in. to	ft.
Casing height above land surface:	12 _{in.,}	Weight:	2.35	bs. / ft.	Wall thickness	or gauge No21	14
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberclass 7, PVC 9, ABS 11. Other (specify)							
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)							
2. Louvered shutter 4. Key p		e wrapped		w cut	10. Other (spec	ifv)	
			-		_		
SCREEN - PERFORATION INTERVAL	From	40 ft.	to 50	ft.,	From ft.		ft.
CDAVE: BACK NITEBYALO	From	ft. 24 ft.	to 50	ft.,	From ft.		ft.
GRAVEL PACK INTERVALS:	From -			ft.,	From ft.		ft.
- L CROUT MATERIALS	From	ft.	to	ft.,	From ft.		ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24 ft.							
Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24 What is the nearest source of possible contamination:						to 24 ft.	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/G							
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)							
3 Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage							
Direction from well? South		00	Гиона	T =	How many feet?		
From To 0 3 topsoil	LITHOLOGIC L	LOG	From	То	LIIF	HOLOGIC LOG	
3 35 fine sand							
35 50 medium sand	1						
				+			
				, , , , , , , , , , , , , , , , , , ,			
				-			
			-	+	****		
				1			
				ļ			
	_ ·		\dashv	1			#-#
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and							
was completed on (mo/day/year) 7/30/2020 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/31/2020							
under the business name of Harp Well and Pump Service by (signature) Todd S. Horp							