		WATER V	VELL RE	CORD	Form WV	VC-5 K	SA 82a-12	212			
1 LOCATION OF WATE	R WELL:	FRACTION			SEC	TION NUMBER		HIP NUMBER	1	E NUMBER	
Sedgwick		SW 1/4		1/4 NE	1/4	30	Т	<b>26</b> s	R	1W E/W	
Distance and direction from 10506 W. Wi				hin city?							
2 WATER WELL		LAUSMEYER	, Kansas .CONST	RUCTION	V		<del></del>	1"		7777	_
RR#,ST. ADDRESS		008 W. York	,consi	ROCTIO	•			Board of Ag	riculture, Division	of Water Resou	ırce
		ichita, Kansas			z	IP CODE: 6	7215	Application Nu	mber:		
3 LOCATE WELL'S L	OCATION	DEPTH OF COM	IPLETED WE	LL:	70 ft.		ELEVATION	:			
WITH AN "X" IN SE	CTION BOX:	<b></b> Depth of groundwat			ft			ft.		ft.	
		WELL'S STATIC V			FT. BELO	W LAND SU	IRFACE MEA	SURED ON mo/	day/yr: 12	2/22/20	
NW	NEX	F	ump test data	a: Well w	ater was		ft. after		s of pumping @	<b>D</b>	gpn
<u>o</u>		Est. Yield:	gpm	Well w	ater was		ft. after	hour	s of pumping @	<b>D</b> 9	gpm
w Wile	E	Bore Hole Diamet	ter 12	in.	to '	70 ft.	and	in.	to	)	ft.
sw	SE	WELL WATER TO				- I aum	and acardon of	9. Dewater	9	njection well	
	:		3. Feedlot				and garden o	יענוי 10. Monitori		(Specify bel	ow
		Irrigation     Was a chemical/bac	<ol> <li>Industrial teriological sam</li> </ol>		water supply	y 8. AIF COI YES	nditioning NO		what mo/day/	yr was sampl	e
		submitted		ipio odbililiod to	оранный:		Vater Well Dis	infected?	YES	NO	
5 TYPE OF CA	SING USED:	5. Wroug	ht Iron	7. Fiberglas	9. C	ther (Specify	below) C	ASING JOINTS:	Glued	Threade	d d
1. Steel	3. RPM	(SR)		•	S.D.	R-26	•		Welded	Clamped	d
2. PVC	> 4. ABS		tos-Cement	8. Concrete	tile SD	10-20					
Blank casing diamet	er <b>5</b>	in. to	50 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height abov		12 <sub>in.,</sub>		Weight:	2.35	lbs. / ft.	Wall	thickness or gau	ge No2	14	
TYPE OF SCREEN	_			7 77 10			44	Other (: E )			
	3. Stainless Stee			7. PVC	9. A			Other (specify)	. b -1-1		
	4. Galvanized	6. Concrete	: IIIe	8. RMP (SR)	10. A	Asbestos-Cer	ment 12.	None used (oper	noie)		
SCREEN OR PERF											
1. Continuous slo		siot 5	i. Gauzed wra	apped	7. To	orch cut	9. D	rilled holes	11. None	e ( open hole	)
2. Louvered shutt	er 4. Key	punched 6	. Wire wrapp	oed	(8. Sa	w cut	10. O	ther (specify)			
SCREEN - PERFOR	ATION INTERVA	L From	50	ft.	to 70	ft.,	From	ft.	to	ft	t.
		From		ft.	to	ft.,	From	ft.	to	fi	t.
GRAVEL PA	ACK INTERVALS	: From	24	ft.	to <b>70</b>	ft.,	From	ft.	to	ft	t.
		From		ft.	to	ft.,	From	ft.	to		t.
6 GROUT MATER	RIALS: 1 Ne	at cement	2 Ceme	ent Grout		3. Bentonite			tonite hole		-
Grout Intervals:	From	ft. to		t., From	ft.		ft.,	From 4	tonice noic	to 24	ft.
What is the nearest s	ource of possible	contamination:	•	.,							14.
1. Septic tank	4. Late	eral lines	7. Pit privy		10. Livesto	•	13. I <b>nse</b>	cticide storage		ell/Gas well	
2. Sewer lines	5. <b>Ces</b>	s Pool	8. Sewage I	•	11. Fuel sto	•	14. <b>Aba</b>	ndon water well	16. Otner	(specify belo	OW)
3. Watertight sew	er line 6. See North	page pit	9. Feed yard	i .	12. Fertilize	r storage					
From To	Torth	LITHOLOG	10100		T F	1 7.	How	many feet? 15			
0 3	topsoil	LITHOLOG	ic Log		From	То		LITHOLO	OGIC LOG	i	_
3 20	clay				+						
20 45	fine sand										
45 70	medium sa	nd									
<del></del>	-				+						
<del></del>											
						<del>                                     </del>					
											_
											_
<del></del>		<u> </u>									
<del></del>						_					
7 Contractor's or	Landowners Co	rtification: This wat	or well was 4	(no. ====================================	<del></del>		4 65 6	plugged	under me : :	diation sed	
		12/23/202				econstructe		plugged	under my juris	SUCUON AND	
was completed or			eu.				knowledge an				
Kansas Water We					well record w	as completed	d on (mo/day/y	rear) 12/2	24/2020		
under the business name of Harp Well and Pump Service by (signature)  Todds. Horb											