			WATER \	NELL RE	CORD	For	m WW	C-5 KS	SA 82a-12	12			
1'1.	1 LOCATION OF WATER WELL: FRACTION						SECT	ION NUMBER					
Sedgy			SE 1/	<u> </u>		IE 1,	/4	30	Т	26 s	R	1W	E/W
1 .	Wilkins	n nearest town or city	o street address of v ze, Kansas		vitnin city? ve B, Eag	tos No	et Ind	A ddition	•)				
TT TT	R WELL O		SEY INVE			163 116	31, ZIIU	Auditio	11)				
 	ADDRESS,		N. 119th St.							Board of Agri	iculture, Division	of Water	Resource
	CITY, S	STATE: Wic	hita, Kansas	3			ZIF	CODE: 6	7235	Application Nun	nber:		
3 LOCATE	WELL'S LO	CATION 4	DEPTH OF CO	MPLETED W	VELL:	85	ft.		ELEVATION				
WITHAN	N"X" IN SEC N		epth of groundwa	ter Encounte	ered:		ft.			ft.			ft.
Π		W	ÆLL'S STATIC V	NATER LEV	EL 20	FI	T. BELOV	W LAND SU	RFACE MEAS	SURED ON mo/o	lay/yr: 1	/28/21	
¹	N₩	-NE-X	ı	Pump test da	ata: Wel	ll water v	was		ft. after	hours	of pumping @	D	gpm
w <u>Wile</u>	}	1	Est. Yield:	gpm		ll water v		_	ft. after	hours	s of pumping @	2)	gpm
	 	1 1	Bore Hole Diame				to 8	6 ft.	and	in.	to		ft.
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	sw	J_	/ELL WATER TO 1. Domestic) BE USED / 3. Feedlot		c water:	supply 9	7. Lawn a	nd garden or	9. Dewateri	··9	injection - (Secol	
	1	1	2. Irrigation	4. Industria			r supply			10. Monitori	12. Other ng well	r (Speci	ly below
'	S	······································	Was a chemical/ba					YES	NO		what mo/day/	•	sample
			ubmitted					Was V	Vater Well Dis	infected?	YES	NO	
	PE OF CAS . Steel	ING USED: 3. RPM (S	5. Wroug	ght Iron	7. Fiberg	lass	9. Ot	her (Specify	below) C/	ASING JOINTS:	Glued		readed
	. PVC	3. RFM (3 3. ABS	•	tos-Cement	8. Concr	ete tile	SDF	R-26			Welded	Cla	amped
_	ng diamete	·	in. to	66 ft.			in.	to	ft.,	Dia.	in. to		ft.
Ĭ.	-	land surface:	12 in		•							1.4	14.
	-	DR PERFORATIO	,		Weight:	L. .	35 ID	s. / ft.	vvaii	thickness or gaug	ge No. Z	14	
1. Stee		. Stainless Steel	5. Fibergla	ss (7. PVC	>	9. AE	38	11. (Other (specify)			
2. Bras	s 4	. Galvanized	6. Concret	e Tile	8. RMP (SR)	10. As	sbestos-Cer	nent 12. I	None used (open	hole)		
SCREEN	OR PERFO	RATION OPENIN	GS ARE:										
1. Contir	nuous slot	3. Mill s	lot	5. Gauzed w	/rapped		7. To r	ch cut	9. D ı	rilled holes	11. Non	e (open	n hole)
2. Louve	red shutte	r 4. Kev r	ounched	6. Wire wrap	ped		(8. Sav	w cut	10. O	ther (specify)			
SCREEN -	DEDECIDA	TION INTERVAL		66	ft.	40	86						
JOOKELIN -	FERFORM	TION INTERVAL	From	00		to	00	ft.,	From	ft.	to .		ft.
ا د	DAVEL DA	CK INTERVALS:	From	24	ft. ft.	to to	86	ft.,	From	ft.	to .		ft.
"	WAVEL PA	CK INTERVALS.	From	27			00	ft.,	From	ft.	to		ft.
a L oper	T MATERI	41.0	From		ft.	to		ft.,	From	ft.	to		ft.
<u> </u>	JT MATERI.	1. 11021	cement		ment Grout			. Bentonite		Other bent	tonite hole		
	ntervals: nearest so	From ource of possible of		to	ft., Fr	om	ft.	to	ft.,	From 4	ft.	to 24	ft.
1. Septio		4. Latera		7. Pit privy	y	10. l	Livestoc	k pens	13. inse	cticide storage	15. Oil w	ell/Gas	well
2. Sewe	r lines	5. Cess	Pool	8. Sewage	lagoon	11.	Fuel stor	age	14. Aba	ndon water well	16. Other	r (specif	iy below)
3. Water	tight sewe		age pit	9. Feed ya	ırd	12.	Fertilizer	storage					
Direction f		South							How	many feet? 50	-		
From	To		LITHOLOG	SIC LOG			From	То		LITHOLO	OGIC LOG	<u> </u>	
3	3 20	topsoil clav	<u></u>										
20	45	fine sand									··············		
45	82	medium san	d										
82	86	clay											
-													
												-	
													
		 				 -		 	<u>. </u>				
7 Cont	rantorie er i	andoumor's Cart	footion: This	Annual :	4	\rightarrow			l	alucas.	umale 1 · 1		
		Landowner's Certi						constructe	-	plugged	under my juri	suiction	and
		(mo/day/year)	1/28/202	41				•	knowledge an				
1		Contractor's Lice				ter well i	record wa	s completed	d on (mo/day/y	rear) 2/0	1/2021		
under th	e business	name of Harp	Well and P	ump Ser	vice		by (si	gnature)	7	rodd S	S. Hau	rb	