

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use

Division of Water Resources App. No.

Well ID

Well ID

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction SE 1/4 SW 1/4 SE 1/4 SE 1/4 Section Number 30 Township Number T 26 S Range Number R 1 E W

2 WELL OWNER: Last Name: Business: ACCEL CONSTRUCTION LLC. Address: 4015 N. WOODLAWN STE# 1 City: WICHITA State: KS ZIP: 67220 Street or Rural Address where well is located: 3815 N. WESTON ST. WICHITA, KS 67101

3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S 1 mile

4 DEPTH OF COMPLETED WELL: 70 ft. Depth(s) Groundwater Encountered: 1) 70 ft. 2) 20 ft. 3) 20 ft. or 4) Dry Well WELLS STATIC WATER LEVEL: 20 ft. below land surface, measured on (mo-day-yr) 3-28-2024

5 Latitude: 37.75248 Longitude: -97.46614 Horizontal Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model: I-PHONE) (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper: Elevation: 70 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID Dewatering: how many wells? Aquifer Recharge: well ID Monitoring: well ID Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 3. Oil Field Water Supply: lease Test Hole: well ID Cased Uncased Geotechnical Geothermal: how many bores? Closed Loop Horizontal Vertical Open Loop Surface Discharge Inj. of Water Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 70 ft., Diameter 12 in. to 70 ft., Diameter 12 in. to 70 ft., Diameter 12 in. to 70 ft. Casing height above land surface 12 in. Weight 2.35 lbs./ft. Wall thickness or gauge No. SDR26 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From 50 ft. to 70 ft., From 50 ft. to 70 ft. GRAVEL PACK INTERVALS: From 24 ft. to 70 ft., From 24 ft. to 70 ft., From 24 ft. to 70 ft., From 24 ft. to 70 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 4 ft. to 24 ft., From 4 ft. to 24 ft., From 4 ft. to 24 ft., From 4 ft. to 24 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? SOUTH Distance from well? 20'+

Table with 6 columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-3 TOP SOIL, 3-23 CLAY, 23-46 FINE SAND, 46-70 MEDIUM SAND. Includes Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 3-28-2024 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo-day-year) 3-29-2024 under the business name of HARP WELL AND PUMP SERVICE INC. Signature TODD S. HARP