


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County <u>Sedgewick</u> Fraction <u>SW 1/4 NE 1/4 SE 1/4</u> Section number <u>1</u> Township number <u>T 26 S</u> Range number <u>R 1 E</u>	
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>2930 W. 72nd No. Wichita KS</u>	
3. Owner of well: <u>Ray Peavey</u> R.R. or street: <u>145 Park Ct</u> City, state, zip code: <u>Valley Center KS 67147</u>	
4. Locate with "X" in section below: Sketch map: <u>Septu</u> 	
5. Type and color of material	
From To	
<u>Top soil</u> 0 3	
<u>red clay</u> 3 11	
<u>fine sand</u> 11 28	
<u>gray clay</u> 28 30	
<u>med to coarse gravel</u> 30 49	
<u>clay</u> 49	
6. Bore hole dia. <u>4 1/2</u> in. Completion date <u>8/29/78</u> Well depth <u>49</u> ft.	
7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Law ☐ Oil field water ☐ Other	
9. Casing: Material <u>Steel</u> Weight <u>12</u> lbs./ft. Threaded <u>X</u> Welded <u>X</u> Surface <u>1 1/2</u> in. RMP <u>X</u> PVC <u>X</u> Weight <u>1.50</u> lbs./ft. Dia. <u>5</u> in. to <u>49</u> ft. depth Wall Thickness <u>1/2</u> inches or Dia. <u>5</u> in. to <u>49</u> ft. depth gage No. <u>200</u>	
10. Screen: Manufacturer's name <u>Sunflower</u> Type <u>200</u> Dia. <u>1 1/2</u> in. Slot gauge <u>1/16</u> Length <u>40 ft</u> Set between <u>39</u> ft. and <u>49</u> ft. Gravel pack <u>yes</u> Size range of material <u>3/8</u>	
11. Static water level: <u>13</u> ft. below land surface Date <u>8/29/78</u> mo./day/yr.	
12. Pumping level below land surfaces: ft. after <u>12</u> hrs. pumping <u>15</u> g.p.m. ft. after <u>12</u> hrs. pumping <u>15</u> g.p.m. Estimated maximum yield <u>50-60</u> g.p.m.	
13. Water sample submitted: <u>X</u> Yes <u>X</u> No Date <u>8/29/78</u> mo./day/yr.	
14. Well head completion: <u>X</u> Pitless adapter <u>12</u> inches above grade	
15. Well grouted? <u>yes</u> With: <u>Neat cement</u> <u>X</u> Bentonite <u>X</u> Concrete Depth: From <u>13</u> ft. to <u>13</u> ft.	
16. Nearest source of possible contamination: <u>100</u> ft. Direction <u>NE</u> Type <u>150</u> Well disinfected upon completion? <u>X</u> Yes <u>X</u> No	
17. Pump: <u>Not installed</u> Manufacturer's name <u>FW</u> Model number <u>12518</u> HP <u>1/2</u> V <u>320</u> Length of drop pipe <u>25</u> ft. capacity <u>12</u> g.p.m. Type: <u>X</u> Submersible <u>—</u> Turbine <u>—</u> Jet <u>—</u> Reciprocating <u>—</u> Centrifugal <u>—</u> Other	
18. Elevation: Topography: <u>X</u> Hill <u>X</u> Slope <u>X</u> Upland <u>—</u> Valley	
19. Remarks: <u>Customer to furnish 4x4x4 ft slab around casing at grade</u> <u>Per State Regulations</u> <u>Signed X Raymond Peavey</u>	
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Business name <u>Wenger Valley</u> License No. <u>318</u> Address <u>Sedgewick KS</u> Signed <u>Wenger</u> Date <u>8/29/78</u> Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5