

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Sedgwick	Fraction 1/4 W 1/2 NE 1/4	Section number 4	Township number T 26 S R 1 NW	Range number
2. Distance and direction from nearest town or city: 1/2 Mi. W. & 1/4 Mi. S. of 77th N. & Ridge Rd. Street address of well location if in city:				3. Owner of well: Clair Evans R.R. or street: Valley Center, Ks. 67147 City, state, zip code:		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 30 in. Completion date 12/2/77 Well depth 146 1/2 ft.		
		Well No. 3 (TH 1-77)		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
5. Type and color of material		From To		9. Casing: Material STL Height: Above <input type="checkbox"/> Below <input checked="" type="checkbox"/> Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 31.25 lbs./ft. Dia. 16 in. to 85 ft. depth Wall thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 13/16"		
				10. Screen: Manufacturer's name Doerr Metal Products Co. Type Steel Dia. 16" Slot/gauze 1/8 Length 64' Set between 48.5 ft. and 68.5 ft. 84.5 ft. and 122.5 ft. Gravel pack? yes Size range of material 1/8 x 1/2		
Top soil		0 2		11. Static water level: 11.7 ft. below land surface Date 12/2/77		
Brown silt		2 8		12. Pumping level below land surfaces: 31.55 ft. after 3 hrs. pumping 1200 g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 2000 g.p.m.		
Med. to co. sand & gravel		8 68		13. Water sample submitted: ____ mo./day/yr. ____ Yes <input checked="" type="checkbox"/> No Date ____		
Gray clay		68 87		14. Well head completion: ____ Pitless adapter 12 inches above grade		
Med. to co. sand to med. co. gravel		87 105		15. Well grouted? yes With: ____ Neat cement ____ Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
Gray clay		105 110		16. Nearest source of possible contamination: ft. 1000 Direction SW Type House Well disinfected upon completion? ____ Yes <input checked="" type="checkbox"/> No		
Fine sand		110 115		17. Pump: ____ Not installed Manufacturer's name Layne & Bowler Model number 12 FL HP 20 Volts 460 Length of drop pipe 40 ft. capacity 1400 g.p.m. Type: ____ Submersible <input checked="" type="checkbox"/> Turbine ____ Jet ____ Reciprocating ____ Centrifugal ____ Other		
Gray clay		115 123		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name Wichita, Kansas License No. ____ Address 1212 S. 1st Date 12/2/77 Signed [Signature] Authorized representative		
Med. to co. sand to med. co. gravel		123 147				
Blue shale		147				
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:				
Topography: ____ Hill ____ Slope ____ Upland <input checked="" type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5