Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction		Se	Section number		Township number Range number			
1. Location of well:	Seelgwick	NW1/4 NE 1/4 NW	N1/4 5		5	т 26 s	R	X EV	
2. Distance and direc		NOB maigh	3. Owner o		· R	obert Ulbrick			
Street address of well	· ba	E by road	R.R. or stre			.R. 1		_	
4. Locate with "X" in	n section below:	Sketch map:	City, state,	, zip c	code: V	alley Center, K	ansas 6714	7	
N	n section below.	skeren map.				Well depth 156 ft:			
X	1					7 Cable tool Rotary	Driven Du	9	
ww -	NE	4 1				Hollow rod Jetted			
w	i E	1				8. Use: Domestic Programmed A			
; i	<u> </u>	,				Lawn O			
SW	SE	E.				9. Casing: Material TRan			
<u> </u>		A				Threaded Welded RMP PVC	iSurface	in.	
1 Mi	le -	♥				Dia. 16 in. to ft. dep	oth!Wall Thickness: i	inches or	
5. Type and color of material				rom	То	Dia. Q in. to 111 ft. depth gage No3/16			
						10. Screen: Manufacturer's I	on		
	Top soi	l to sandy clay		۵	_5_	Type sawed	_ Dia 16		
	*			5	50	Slot/gauze 3/16 Set between 117	_ Length 39		
	Med. to	coarse sand		2		ft.c	ft. and 1360 ond	!†.	
	Fine to	med. sand w/clay		50	60	Gravel pack? Yes Size ra	nge of material 1/	8-#	
	fina car	nd and clay	6	0	75	11. Static water level:		o./day/yr.	
		5				ft. below land sur		///	
	Brown sa	indy clay		75	90	49 ft. after	nrs. pumping 80	Q _{g.p.m.}	
	Med. to	fine sand		90	95	68 ft. after 2	nrs, pumping 140		
	37.3 L	0:		<u></u>	,,,,	Estimated maximum yield		g.p.m.	
	med. to	fine sand w/clay		72	100	Vas No	Data		
	Fineesar	nd w/ clay	1	00	105	14. Well head completion: Pitless adapter	₹		
	Hard bro	num claw	17	05	110 F		<u> </u>	e grade	
						15. Well grouted? With: Negt cement	Bentonite	Concrete	
	Fine sar	nd w/clay	1	10	115	Depth: From ft. to	70 H. T		
	Fine to	med. sand with cla	ay 1	15	120	16. Nearest source of possible ft Direction	contamination:		
			·	20	130	Well disinfected upon comple		X No	
	Med. sar	nd w/little clay		Ī		17. Pump:	Not installed		
	Coarse s	sand w/clay	1	30	135	Manufacturer's nameWest		oller	
	Med. to	coarse sand		35	145	Length of drop pipe	ft. capacity	X 3.p.m.	
	11000	<u> </u>		-		Type:			
	Med. to	fine sand verylit	tle l	45	150	Submersible Jet	<u>X</u> Turbir Recip	ne rocating	
	(Use a seco	nd sheet if neededine sand		50l	155	Centrifugal	Other	· · · · · · · · · · · · · · · · · · ·	
8. Elevation:	19. Remarks: Fine sar	nd to blue shale			160	20. Water well contractor's of This well was drilled under m			
						is true to the best of my know	•	is report	
Topography:	Patt	en of well	1,5	56		Darling Drilling	ng Co. 189		
Hill Slope	₩.W	5				Address 121 W. 4tl	Hutchine	cense No. on Kan	
Upland						Signed Donald	ON all	30	
Valley						Authorized rep	esendative	vuay	