


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SE 1/4 SE 1/4 NE 1/4		Section Number 9		Township Number T 26 S		Range Number R 1 W 1/2											
Distance and direction from nearest town or city street address of well if located within city? 6611 North Ridge Road Wichita, Kansas																			
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Knebler Co., Inc. P.O. BOX 454 Augusta, KS. 67010 Board of Agriculture, Division of Water Resources Application Number:																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 7-7-86 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Lawn and garden</u> only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... XX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No																
			5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped 2 PVC 160 PSI 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 8 in. to 25 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 12 in. weight 5.47 lbs./ft. Wall thickness or gauge No. 332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 <u>PVC</u> 160 PSI 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped <u>8 Saw cut</u> 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25 ft. to 45 ft., From ft. to ft. From 65 ft. to 85 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 14 ft. to 85 ft., From ft. to ft. From ft. to ft., From ft. to ft.																
										6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage <u>None apparent</u> Direction from well? How many feet?									
FROM			TO			LITHOLOGIC LOG				FROM			TO			LITHOLOGIC LOG			
0			3			Topsoil													
3			17			Fine Sand													
17			23			Clay													
23			45			Medium Sand													
45			48			clay													
48			65			Fine Sand													
65			85			Medium Sand													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-7-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 7-7-86 under the business name of Harp Well & Pump Service, Inc. by (signature) <u>Mary Arnold</u>																			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.																			

OFFICE USE ONLY

T

R

EAW

SEC.

1/4

1/4

1/4