


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NW 1/4 NE 1/4 NE 1/4	13	T 26 S	R 1W EW

Distance and direction from nearest town or city street address of well if located within city?

2805 W. 60th N. Fox Meadows Add. Blk. 3 Lot 28 Wichita, Ks.

2 WATER WELL OWNER:	Pate Construction	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	12412 Walker	Application Number:
City, State, ZIP Code :	Wichita, Ks.	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 12 ft. 2. 12 ft. 3. 12 ft.
	WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 3-19-90
	Pump test data: Well water was 11 ft. after 43 hours pumping 11 gpm
	Est. Yield 11 gpm: Well water was 43 ft. after 11 hours pumping 11 gpm
	Bore Hole Diameter 11 in. to 43 ft., and 11 in. to 43 ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	11 Injection well
Blank casing diameter 5 in. to 33 ft., Dia.			12 Other (Specify below)
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 33 ft. to 43 ft.	From 33 ft. to 43 ft.	From 33 ft. to 43 ft.
GRAVEL PACK INTERVALS:	From 24 ft. to 43 ft.	From 24 ft. to 43 ft.	From 24 ft. to 43 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft.				
What is the nearest source of possible contamination:	septic system not installed at this time			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None Apparent

Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	7	clay			
7	17	fine sand			
17	27	medium sand			
27	32	clay (grey)			
32	43	medium sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-19-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-10-90 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold
