


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 17 Township Number T 26 S Range Number R 1 W
 County: Sedgewick
 Distance and direction from nearest town or city street address of well if located within city? 1 EAST K No MAILE KS.

2 WATER WELL OWNER: Bob PRESS
 RR#, St. Address, Box #: 4121 E. CLARK
 City, State, ZIP Code: WICHITA KS 67218
 Board of Agriculture, Division of Water Resources
 Application Number: 39824

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 12 ft. below land surface measured on mo/day/yr 6-18-90
 Depth(s) Groundwater Encountered: 1 ft. 14 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 6-18-90
 Pump test data: Well water was 12 ft. after 20 hours pumping 200 gpm
 Est. Yield 200 gpm Well water was 12 ft. after 20 hours pumping 200 gpm
 Bore Hole Diameter: 11 in. to 50 ft. and 50 in. to 50 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted No
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 5 ft. Dia. 5 in. to 5 ft. Dia. 5 in. to 5 ft.
 Casing height above land surface: 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft. From 30 ft. to 50 ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 50 ft. From 15 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 15 ft. From 15 ft. to 50 ft. From 50 ft. to 50 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) OPEN FIELD
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top 50: 1			
2	10	clay			
10	29	fine sand			
29	30	clay			
30	50	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-18-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/year) July 2, 90 under the business name of Wenings Dully by (signature) [Signature]