

1 LOCATION OF WATER WELL: County: Sedg. Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 18 Township Number: T 26 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city: 1 No MAIZE KS

2 WATER WELL OWNER: RR#, St. Address, Box #: C.L. Banta Board of Agriculture, Division of Water Resources
City, State, ZIP Code: 6131 No maize rd Application Number: maize ks

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
	SW	SE	E
S			

4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: 12 ft.

Depth(s) Groundwater Encountered: 1. 12 ft. 2. 12 ft. 3. 12 ft.

WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 8-28-82

Pump test data: Well water was 12 ft. after 12 hours pumping 10 gpm

Est. Yield: 50 gpm. Well water was 12 ft. after 12 hours pumping 10 gpm

Bore Hole Diameter: 11 in. to 33 ft., and 33 in. to 33 ft.

WELL WATER TO BE USED AS:

☒ Domestic	3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only	9 Dewatering	12 Other (Specify below)
			10 Observation well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

1 Steel	☒ 3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>X</u>
		7 Fiberglass		Threaded <u>X</u>

Blank casing diameter: 5 in. to 25 ft., Dia. 5 in. to 25 ft.

Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	☒ 8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	☒ 3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 25 ft. to 33 ft., From 25 ft. to 33 ft., From 25 ft. to 33 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 33 ft., From 13 ft. to 33 ft., From 13 ft. to 33 ft.

6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	☒ 8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? West

How many feet? 130

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	12	Red clay			
12	33	med gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-29-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 9-1-82 under the business name of Wenger, Pulley by (signature) Wenger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

E

SEC.

18

NE 1/4

NE 1/4

NE 1/4

NE 1/4