


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 19 Township Number T 26 S Range Number R 1 E  
 County: Sedg Distance and direction from nearest town or city street address of well if located within city? See Below.

2 WATER WELL OWNER: Brian Klusnee  
 RR#, St. Address, Box #: 643 Queen Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: MAIZE KS. Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL 51 ft. ELEVATION: 5-5-94  
 Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft.  
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 5-5-94  
 Pump test data: Well water was 18 ft. after 12 hours pumping 20 gpm  
 Est. Yield 40 gpm Well water was 18 ft. after 12 hours pumping 20 gpm  
 Bore Hole Diameter 11 in. to 51 ft. and 51 in. to 51 ft.  
 WELL WATER TO BE USED AS:  
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)  
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:  
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped  
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded  
☐ 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 41 ft. Dia. 41 in. to 41 ft. Dia. 41 in. to 41 ft. Dia. 41 in. to 41 ft.  
 Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement  
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify)  
☐ 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)  
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes  
☐ 7 Torch cut ☐ 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 41 ft. to 51 ft. From 41 ft. to 51 ft. From 41 ft. to 51 ft. From 41 ft. to 51 ft.  
 GRAVEL PACK INTERVALS: From 23 ft. to 51 ft. From 23 ft. to 51 ft. From 23 ft. to 51 ft. From 23 ft. to 51 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other  
 Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 51 ft. From 51 ft. to 51 ft. From 51 ft. to 51 ft.  
 What is the nearest source of possible contamination:  
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well  
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well  
☒ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)  
☐ 13 Insecticide storage  
 Direction from well? North How many feet? 15

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|----------------|------|----|--------------------|
| 0    | 2  | Top soi        |      |    |                    |
| 2    | 17 | clay           |      |    |                    |
| 17   | 30 | fine sand      |      |    |                    |
| 30   | 31 | clay           |      |    |                    |
| 31   | 51 | gravel         |      |    |                    |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-5-94 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-26-94  
 under the business name of Weninger Dully by (signature) [Signature]