


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 19 Township Number T 26 S Range Number R 1 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
See Below

2 WATER WELL OWNER: Victor Bolton
 RR#, St. Address, Box #: 11407 W. 53rd No
 City, State, ZIP Code: MAIZE KS 67101
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 20 ft. 2. 40 ft. 3. 6-3-94 ft.
 WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 40 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 30 gpm: Well water was 40 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 70 ft., and 70 in. to 70 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)
☒ 2 PVC ☐ 4 ABS ☐ 7 Fiberglass
 Blank casing diameter 5 in. to 60 ft. Dia. 60 in. to 60 ft. Dia. 60 in. to 60 ft. Dia. 60 in. to 60 ft. Dia.
 Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 60 ft. to 70 ft. From 60 ft. to 70 ft. From 60 ft. to 70 ft. From 60 ft. to 70 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 70 ft. From 23 ft. to 70 ft. From 23 ft. to 70 ft. From 23 ft. to 70 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 20 ft. From 50 ft. to 60 ft. From 50 ft. to 60 ft. From 50 ft. to 60 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☒ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? North
 How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soi.			
2	16	clay.			
16	20	fine sand.			
20	33	med sand.			
33	37	clay.			
37	51	med sand.			
51	58	clay			
58	68	gravel			
68	70	clay.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-3-94 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 378 This Water Well Record was completed on (mo/day/yr) 6-13-94
 under the business name of Weningshully by (signature) [Signature]