

1 LOCATION OF WATER WELL: County: Sedgewick Fraction: SW 1/4 NE 1/4 Section Number: 19 Township Number: T 26 S Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city?
112 Heather Maize Rd
Dowell Homes
5065 Primrose
Wichita KS 67219

2 WATER WELL OWNER: RR#, St. Address, Box # :
City, State, ZIP Code :
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N
W
E
S
1 Mile
SW NW NE SE
SE

4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 16 ft. below land surface measured on mo/day/yr 5-18-85
Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 20 ft.
WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 5-18-85
Pump test data: Well water was 16 ft. after 1 1/2 hours pumping 20 gpm
Est. Yield 50 gpm: Well water was 16 ft. after 1 1/2 hours pumping 20 gpm
Bore Hole Diameter 1 1/2 in. to 36 ft. and 36 in. to 36 ft.
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
Blank casing diameter 5 in. to 26 ft. Dia 5 in. to 26 ft. Dia 5 in. to 26 ft. Dia 5 in. to 26 ft. Dia
Casing height above land surface 1 1/2 in. weight 1 59 lbs./ft. Wall thickness or gauge No. SDR-26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From 26 ft. to 36 ft. From 26 ft. to 36 ft. From 26 ft. to 36 ft.
GRAVEL PACK INTERVALS: From 13 ft. to 36 ft. From 13 ft. to 36 ft. From 13 ft. to 36 ft. From 13 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 36 ft. From 13 ft. to 36 ft. From 13 ft. to 36 ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? EAST
How many feet? 20

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	top soil			
2	15	clay			
15	36	sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-18-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-18-85 under the business name of Dowell Homes by (signature) Dowell Homes

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

E

SEC.

19

SW 1/4

NE 1/4

NE 1/4