


1 LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 NE 1/4 NE 1/4 Section Number: 19 Township Number: T 26 S Range Number: R 10 E
Distance and direction from nearest town or city street address (if well is located within city): 108 Heather Maye Dr.

2 WATER WELL OWNER: RR#, St. Address, Box #: Powell Homes
City, State, ZIP Code: 5065 Prairie W. Wichita KS 67219 Board of Agriculture, Division of Water Resources Application Number: _____

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: _____
Depth(s) Groundwater Encountered 1. 16 ft. 2. _____ ft. 3. _____ ft.
WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr 5-18-85
Pump test data: Well water was _____ ft. after 1 1/2 hours pumping 20 gpm
Est. Yield 50 gpm: Well water was _____ ft. after _____ hours pumping _____ gpm
Bore Hole Diameter: 1 1/2 in. to 3.6 ft., and _____ in. to _____ ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes _____ No X If yes, mo/day/yr sample was submitted _____
Water Well Disinfected? Yes X No _____

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped _____
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded _____
Blank casing diameter 5 in. to 26 ft. Dia. _____ in. to _____ ft. Dia. _____ in. to _____ ft.
Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) _____
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) _____
SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft., From _____ ft. to _____ ft.
GRAVEL PACK INTERVALS: From 13 ft. to 36 ft., From _____ ft. to _____ ft.
From _____ ft. to _____ ft., From _____ ft. to _____ ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____
Grout Intervals: From 3 ft. to 13 ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? North How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	15	Clay			
15	36	Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-18-85 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-18-85
under the business name of Wenger's Dolly by (signature) James Wenger
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

ED

SEC.

19

SW 1/4

NE 1/4

NE 1/4

1/4