


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 NE 1/4 NE 1/4	19	T 26 S	R 1 NE
Distance and direction from nearest town or city street address of well if located within city? 208 N Queen Maize KS					

2 WATER WELL OWNER: Huffman, Bob		Board of Agriculture, Division of Water Resources Application Number: NA
RR#, St. Address, Box #: 840 S WYLYN City, State, ZIP Code: MAIZE KS 67101		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 31 ft. ELEVATION: 7'-6"	
	Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft.	
	WELL'S STATIC WATER LEVEL: 7'-6" ft. below land surface measured on mo/day/yr 5-1-84	
	Pump test data: Well water was 9'-6" ft. after 1 1/2 hours pumping 30 gpm Est. Yield 60 gpm: Well water was 9'-6" ft. after 1 1/2 hours pumping 30 gpm Bore Hole Diameter: 9 in. to 7'-6" ft., and 9 in. to 7'-6" ft.	
WELL WATER TO BE USED AS: ☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well		
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted 5-1-84 Water Well Disinfected? Yes ☒ No ☐		

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☐ Clamped ☐
1 Steel	☒ 3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded ☐
2 PVC	4 ABS	7 Fiberglass		Threaded ☐
Blank casing diameter: 6 in. to 27 ft. Dia.		in. to 1.95 ft. Dia.		
Casing height above land surface: 12 in. weight 1.95 lbs./ft. Wall thickness or gauge No. sch 200				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	☒ 8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	☒ 8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS:				
From 27 ft. to 32 ft.		ft. to 32 ft.		
GRAVEL PACK INTERVALS:				
From 27 ft. to 32 ft.		ft. to 32 ft.		

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	☒ 3 Bentonite	4 Other
Grout Intervals: From 3 ft. to 7'-6" ft.		ft. to 7'-6" ft.			
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
☒ 3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well? North		How many feet? 19			

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Drk. Brn. Clay			
3	5	LT. " "			
5	9	Gray " "			
9	20	LT. TAN COARSE GRAVEL			
9	20	Gray fine sand			
20	32	LT. TAN COARSE GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-1-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 295 This Water Well Record was completed on (mo/day/yr) 5-1-84 under the business name of Protheroe Pump & Well by (signature) John Protheroe	
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.	

OFFICE USE ONLY

T

26

R

E

SEC.

19

S

NE

1/4

1/4