


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 SE 1/4 NE 1/4	Section Number 19	Township Number T 26 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 228 East Liberty, Maize, KS					
2 WATER WELL OWNER: Lawrence Doughty RR#, St. Address, Box #: 228 East Liberty City, State, ZIP Code: Maize, Kansas 67101			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 17 ft. 2. 17 ft. 3. 17 ft. WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on July 9, 1987 Pump test data: Well water was 17 ft. after 2 hours pumping 20 gpm Est. Yield 11 gpm Well water was 17 ft. after 2 hours pumping 20 gpm Bore Hole Diameter 11 in. to 50 ft., and 50 in. to 50 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 50 ft., Dia. 1.59 in. to 50 ft., Dia. 1.59 in. to 50 ft. Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From 30 ft. to 50 ft., From 30 ft. to 50 ft. GRAVEL PACK INTERVALS: From 23 ft. to 50 ft., From 23 ft. to 50 ft., From 23 ft. to 50 ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 23 ft., From 3 ft. to 23 ft., From 3 ft. to 23 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South How many feet? 20					
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 2 Top soil					
2 14 clay					
14 29 Sand (fine)					
29 30 clay					
30 50 gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-9-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) July 9, 1987 under the business name of WENINGER DRILLING by (signature) James W. Weninger INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EAW

SEC.

1/4

1/4

1/4