


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 19	Township Number T 26 S	Range Number R 1W
Distance and direction from nearest town or city street address of well if located within city? 308 Harvest Ln. Maize, Ks.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Board of Agriculture, Division of Water Resources Application Number: Delbert Goertz Constr. 4401 N. Maize Rd. Maize, Ks			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 5-14-90 Pump test data: Well water was 11 in. to 40 ft., and 40 in. to 40 ft. Est. Yield 11 gpm: Well water was 40 ft. after 40 hours pumping 11 gpm Bore Hole Diameter 11 in. to 40 ft., and 40 in. to 40 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 2 PVC160 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 5 in. to 40 ft., Dia. 5 in. to 40 ft., Dia. 5 in. to 40 ft. Casing height above land surface 1.2 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 30 7 Torch cut 40 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From 30 ft. to 40 ft., From 30 ft. to 40 ft. GRAVEL PACK INTERVALS: From 24 ft. to 40 ft., From 24 ft. to 40 ft., From 24 ft. to 40 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 24 ft., From 4 ft. to 24 ft., From 4 ft. to 24 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 11 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 3 topsoil 3 18 clay 18 27 fine grey sand 27 29 clay 29 40 medium sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-14-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-31-90 under the business name of Harp Well and Pump Service, Inc. by (signature) <i>Mary Arnold</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					