

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SW 1/4 Section Number 22 Township Number T 26 S Range Number R 1 EW
 County: SEDGWICK
 Distance and direction from nearest town or city street address of well if located within city?
7001 W 49th NORTH, WICHITA KANS

2 WATER WELL OWNER: HARLON POTTS 67205
 RR#, St. Address, Box # :
 City, State, ZIP Code : 7001 W 49th NORTH, WICHITA, KS Board of Agriculture, Division of Water Resources
 Application Number: NO NE

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N				
	NW		NE	
		X		
	SW		SE	
W				E
		S		

4 DEPTH OF COMPLETED WELL: 39 ft. ELEVATION: 1300 ft.
 Depth(s) Groundwater Encountered 1. 11 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 10-23-85
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 50 gpm Well water was NA ft. after NA hours pumping NA gpm
 Bore Hole Diameter 9 in. to 10 ft. and 6 in. to 39 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes NO; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes YES No

5 TYPE OF BLANK CASING USED: 3 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel ② RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 32 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SOR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass ⑥ RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot ③ Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 31 ft. to 39 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.
 From NONE ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement ② Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 18 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 ② Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 ③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? EAST How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	SANDY SOIL, BLACK			
3	6	WHITE SAND - FINE			
6	13	TAN SAND MED.			
13	16	BROWN SAND COARSE			
16	18	MED SAND TAN			
18	19	FINE BROWN SAND			
19	23	VERY COARSE GRAY			
23	27	SAND W/ GRAY CLAY BALLS			
27	29	FINE GRAY SAND			
29	39	COARSE BROWN SAND			
		COARSE SAND, TAN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-23-85 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 12-27-85
 under the business name of BEARDEN Pump & Well by (signature) Otis W. Bearden
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.