


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SW 1/4 Section Number 22 Township Number T 26 S Range Number R 1 E
 County: Sedgewick
 Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: CHARLES ELLIOTT
 RR#, St. Address, Box #: 4926 N. RIDGE RD
 City, State, ZIP Code: WICHITA KS 67205
 Board of Agriculture, Division of Water Resources
 Application Number: 3-1-88

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 812 ft.
 Depth(s) Groundwater Encountered 1. 8 ft. 2. 12 ft. 3. 3-1-88 ft.
 WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 3-1-88
 Pump test data: Well water was 8 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 100 gpm: Well water was 8 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter: 11 in. to 95 ft., and 11 in. to 95 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued X Clamped X
 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ Welded X
 3 Fiberglass ☐ Threaded X
 Blank casing diameter 5 in. to 78 ft., Dia. 12 in. to 1.59 lbs./ft. Wall thickness or gauge No. 50R-26
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 50R-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐
 12 None used (open hole) ☐
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 78 ft. to 95 ft., From 78 ft. to 95 ft.
 GRAVEL PACK INTERVALS: From 73 ft. to 95 ft., From 73 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other ☐
 Grout intervals: From 53 ft. to 73 ft., From 3 ft. to 23 ft., From 23 ft. to 95 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage ☐
 Direction from well? South
 How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	7	Clay			
7	44	Sand			
44	47	Clay			
47	70	Sand			
70	74	Clay			
74	95	med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-1-88 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 3-1-88 This Water Well Record was completed on (mo/day/yr) 3-2-88
 under the business name of Werninger Dutton by (signature) [Signature]
 INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9366. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4