


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SW 1/4 Section Number 22 Township Number T 26 S Range Number R 1 E W  
 County: Sedgwick  
 Distance and direction from nearest town or city street address of well if located within city?  
See Below

2 WATER WELL OWNER: MIKE YOUNKIN  
 RR#, St. Address, Box # : 4959 NO Sierra  
 City, State, ZIP Code : Wich. ta KS 67205  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 11-27-89  
 Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft.  
 WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 11-27-89  
 Pump test data: Well water was 10 ft. after 12 hours pumping 20 gpm  
 Est. Yield 70 gpm: Well water was 10 ft. after 12 hours pumping 20 gpm  
 Bore Hole Diameter 11 in. to 36 ft., and 11 in. to 36 ft.  
 WELL WATER TO BE USED AS:  
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)  
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:  
 1 Steel ☒ 3 RMP (SR)  
 2 PVC ☐ 4 ABS  
 5 Wrought iron ☐ 8 Concrete tile  
 6 Asbestos-Cement ☐ 9 Other (specify below)  
 7 Fiberglass  
 Casing joints: Glued X Clamped X  
 Welded X  
 Threaded X  
 Blank casing diameter 5 in. to 27 ft., Dia. 5 in. to 27 ft., Dia. 5 in. to 27 ft.  
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 7 PVC  
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR)  
 9 ABS  
 10 Asbestos-cement  
 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot ☐ 3 Mill slot  
 2 Louvered shutter ☐ 4 Key punched  
 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)  
 6 Wire wrapped ☐ 9 Drilled holes  
 7 Torch cut ☐ 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 27 ft. to 36 ft., From 27 ft. to 36 ft., From 27 ft. to 36 ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 36 ft., From 20 ft. to 36 ft., From 20 ft. to 36 ft.

6 GROUT MATERIAL: ☒ 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other  
 Grout Intervals: From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft.  
 What is the nearest source of possible contamination:  
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well  
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well  
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)  
☐ 13 Insecticide storage  
 Direction from well? South  
 How many feet? 60

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|----------------|------|----|--------------------|
| 0    | 2  | Top soil       |      |    |                    |
| 2    | 4  | clay           |      |    |                    |
| 4    | 17 | fine sand      |      |    |                    |
| 17   | 20 | clay           |      |    |                    |
| 20   | 36 | SAND           |      |    |                    |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-27-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11-28-89 under the business name of Weninger Duller by (signature) [Signature]