

1 LOCATION OF WELL: County: <u>Sedgewick</u> Fraction: <u>NE 1/4 NW 1/4 SW 1/4</u> Section Number: <u>22</u> Township Number: <u>T 26 S</u> Range Number: <u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>SAME</u>	
2 WATER WELL OWNER: <u>Phil Stover</u> Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #: <u>6929 W. 48th N</u> Application Number:	
City, State, ZIP Code: <u>Wichita, KS 67203</u>	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>50</u> ft. ELEVATION: <u>1022.91</u> ft.
	Depth(s) Groundwater Encountered 1. <u>13</u> ft. 2. <u>13</u> ft. 3. <u>13</u> ft.
	WELL'S STATIC WATER LEVEL <u>13</u> ft. below land surface measured on mo/day/yr <u>10-22-91</u>
	Pump test data: Well water was <u>13</u> ft. after <u>1/2</u> hours pumping <u>20</u> gpm
	Est. Yield <u>13</u> gpm: Well water was <u>13</u> ft. after <u>1/2</u> hours pumping <u>20</u> gpm
	Bore Hole Diameter <u>11</u> in. to <u>50</u> ft., and <u>50</u> in. to <u>50</u> ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <u>X</u> No <u>X</u>	
5 TYPE OF BLANK CASING USED:	
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped	
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded	
Blank casing diameter <u>3</u> in. to <u>40</u> ft., Dia <u>40</u> in. to <u>40</u> ft., Dia <u>40</u> in. to <u>40</u> ft.	
Casing height above land surface <u>12</u> in., weight <u>21.60</u> lbs./ft. Wall thickness or gauge No. <u>160PVC</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:	
1 Continuous slot 3 Mill slot 40 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
2 Louvered shutter 4 Key punched 40 6 Wire wrapped 9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>50</u> ft., From <u>40</u> ft. to <u>50</u> ft., From <u>40</u> ft. to <u>50</u> ft.	
GRAVEL PACK INTERVALS: From <u>13</u> ft. to <u>50</u> ft., From <u>13</u> ft. to <u>50</u> ft., From <u>13</u> ft. to <u>50</u> ft.	
6 GROUT MATERIAL:	
1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From <u>3</u> ft. to <u>13</u> ft., From <u>13</u> ft. to <u>50</u> ft., From <u>50</u> ft. to <u>50</u> ft.	
What is the nearest source of possible contamination:	
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)	
Direction from well? <u>South</u> How many feet? <u>600</u>	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 3 top soil	
3 15 Fine sand	
15 21 clay	
21 35 Med. Sand	
35 39 clay	
39 50 Med Sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-22-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>11-20-91</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>[Signature]</u>	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send up three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.	

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4