


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction: <u>NE 1/4 NE 1/4 NW 1/4</u> Section Number: <u>27</u> Township Number: <u>T 26 S</u> Range Number: <u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>6601 W. 45th North Wichita KS</u>	
2 WATER WELL OWNER: <u>Kirk Woodard</u> Board of Agriculture, Division of Water Resources RR#, St. Address, Box #: <u>6601 W. 45th No.</u> Application Number: City, State, ZIP Code: <u>Wichita 67205</u>	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>103</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>22</u> ft. 2. <u>22</u> ft. 3. <u>22</u> ft. WELL'S STATIC WATER LEVEL <u>22</u> ft. below land surface measured on mo/day/yr <u>12-15-86</u> Pump test data: Well water was <u>22</u> ft. after <u>12</u> hours pumping <u>20</u> gpm Est. Yield <u>75</u> gpm: Well water was <u>22</u> ft. after <u>12</u> hours pumping <u>20</u> gpm Bore Hole Diameter <u>11</u> in. to <u>10.3</u> in. and <u>10.3</u> in. to <u>10.3</u> in. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter <u>5</u> in. to <u>8.75</u> in. Dia. <u>1.2</u> in. weight <u>11.59</u> lbs./ft. Wall thickness or gauge No. <u>SAR-26</u> 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> Welded <u>X</u> Threaded <u>X</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Stainless steel 4 Galvanized steel 3 Mill slot 4 Key punched 5 Fiberglass 6 Concrete tile 7 Torch cut 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN-PERFORATED INTERVALS: From <u>87</u> ft. to <u>103</u> ft. From <u>103</u> ft. to <u>103</u> ft. GRAVEL PACK INTERVALS: From <u>13</u> ft. to <u>50</u> ft. From <u>50</u> ft. to <u>103</u> ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>13</u> ft. From <u>50</u> ft. to <u>55</u> ft. From <u>55</u> ft. to <u>55</u> ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? <u>SE</u> How many feet? <u>90</u>	
FROM TO LITHOLOGIC LOG	FROM TO LITHOLOGIC LOG
0 2 Top soil	75 82 fine sand.
2 12 Clay	82 83 clay
12 31 Sand	83 103 med gravel
31 32 clay	103 - Shale
32 48 sand	
48 69 clay	
69 74 fine sand	
74 75 Clay	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-18-86</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>1318</u> This Water Well Record was completed on (mo/day/yr) <u>12-18-86</u> under the business name of <u>Weninger Drilling</u> by (signature) <u>[Signature]</u>	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.	

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4