

1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 SW 1/4 Section Number 36 Township Number 26 Range Number 1 E/W W
County Sedg
Distance and direction from nearest town or city street address of well if located within city? 3180 No West Street Wichita KS

2 WATER WELL OWNER: Beardt Drilling
RR#, St. Address, Box #: 1200 Douglas Bldg
City, State, ZIP Code: Wichita KS 67202
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N
NW NE
SW SE
S
W E
1 Mile

4 DEPTH OF COMPLETED WELL: 44 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 11 ft. 2. 11 ft. 3. 11 ft.
WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on 8-2-85 mo/day/yr
Pump test data: Well water was 11 ft. after 12 hours pumping 20 gpm
Est. Yield 200 gpm: Well water was 11 ft. after 12 hours pumping 20 gpm
Bore Hole Diameter 11 in. to 44 ft., and 44 in. to 44 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes X No X
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 5 in. to 24 ft., Dia 24 in. to 1.59 lbs./ft. Wall thickness or gauge No SDR-26
Casing height above land surface 24 in., weight 1.59 lbs./ft. Wall thickness or gauge No SDR-26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
3 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 24 ft. to 44 ft. From 44 ft. to 44 ft.
GRAVEL PACK INTERVALS: From 15 ft. to 44 ft. From 44 ft. to 44 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 15 ft. From 15 ft. to 44 ft. From 44 ft. to 44 ft. From 44 ft. to 44 ft.
What is the nearest source of possible contamination: NONE OPEN FIELD 10 Landfills
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top so.			
2	4	clay			
4	20	SAND			
20	21	clay			
21	44	SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-2-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/year) 8-2-85 under the business name of Weninger Drilling by (signature) Weninger
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.