

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.


Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Reno Fraction 1/4 Sec 2, 1/4 NE 1/4, 1/4 SW 1/4 Section Number 13 Township Number T 26 S Range Number R 10 E W

2 WELL OWNER: Last Name: Dickens Jr. First: Paul Business: Address: 110359 NE 141st Ave City: Turon State: KS ZIP: 67583 Street or Rural Address where well is located: Hwy 66 + W 2nd Ave rd - Go East 3.77 miles to S Okant Rd then go south 1.67 miles + East into 268 feet

3 LOCATE WELL WITH "X" IN SECTION BOX: N



4 DEPTH OF COMPLETED WELL: 35 ft. Depth(s) Groundwater Encountered: 1) ... ft. 2) ... ft. 3) ... ft., or 4) Dry Well WELL'S STATIC WATER LEVEL: 10 ft.

5 Latitude: 37.78124 Longitude: -98.366194 Horizontal Datum: WGS 84 Source for Latitude/Longitude: GPS (unit make/model): Online Mapper: Google Earth Pro

6 Elevation: ... ft. Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: Household, Lawn & Garden, Livestock, Irrigation, Feedlot, Industrial. 2. Public Water Supply, Dewatering, Aquifer Recharge, Monitoring, Environmental Remediation, Air Sparge, Recovery, Injection. 3. Oil Field Water Supply, Test Hole, Geothermal, Closed Loop, Open Loop, Other (specify).

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter: 5 in. to 33 ft. Diameter: in. to ft. Casing height above land surface: 24 in. Weight: lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 39 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 35 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout intervals: From 0 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Pond Direction from well? SE + North Distance from well? 100 + 300 ft.

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows show depth intervals from 0 to 35 feet with lithology descriptions like Black Clay, Tan Clay, Coarse Gravel.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 3/16/22 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 679 This Water Well Record was completed on (mo-day-year) 3/13/22 under the business name of Crowds Water Well Signature