10		VVA	TER WELL REC	CORD	Form \	WWC-5		82a-1212 I		<u></u>					
LOCATI	ON OF WA	TER WELL:	Fraction					ction Numb	er		ship Nur			nge Numbe	
County: F			1/4	110	1/4	1111	1/4	9		Т	26	S	R	11	
			own or city stree			if located	within c	city?							
			1 1/4 miles east	of Presto	n										
2 WATER	WELL ON	VNER: Norman	Hildebrand												
RR#, St. A	ddress, Bo	x#:Route 1	- Box 114											of Water Re	esources
City, State,												mber: 4	0,166		
3 LOCATE	WELL'S L	OCATION WITH	4 DEPTH OF	COMPLE	ETED WI	ELL	74	ft. ELE	OITAV	N: unkn	iown				
AN "X"	IN SECTIO	IN BOX:			_				. . –			ft. 3			. ft.
<u> </u>	- 		Depth(s) Groun	WATER	RLEVEL	41	ft. be	low land sur	face me	asured (on mo/da	ay/yr 10-	20-00	 -	
T) Nac	1		•				t checked				-			
	- NVV	NE	Est. Yield _ unk												
₩ W	i	_	Bore Hole Diam	eter	_24	in. to		7 <u>2</u> 1	ft., and ₋			. i	in. to 💄		ft.
₹ W	1	E	WELL WATER T	TO BE US	ED AS:	5 Pub	lic water	supply	8 <i>A</i>	Air conditi	oning	11	Injec	tion well	
	1	<u> </u>	1 Domestic	3 Fe	edlot	6 Oil f	ield wate	r supply	9 0	Dewaterin	g	12	2 Othe	r (specify bel	ow)
	- SW	SE	2 Irrigation	4 Inc	dustrial	7 Don	nestic (la	wn & garden)	10 N	Monitorino	well				
†	i	i	Was a chemical/				,	• ,		_	_ /	if yes m		e samnle v	 vae eub-
- L	5		mitted	Dacterioic	igicai sai	libie subiliti	iteu to D					Yes			√
5 TYPE O	F BLANK (CASING USED:		5 \\/rou	ght iron	8	Concr							Clamped	
1 Steel	, DEFINITE	3 RMP (SR)			stos-Ceme	_		(specify below							
2 PVC		4 ABS			glass				-			Threa	ided		
	ina diamete	er 10	in to	56	•			in. to					in to		ft
		land surface	in. to		_	- 7	80		he /ft M	Vall thick	ness or	gauge No	'''. W		
_	-			in., weigh				'	DS./11. V		_			505	
			TION MATERIAL				PVC	(0.0)				tos-cement			
_	1 Steel 3 Stainless steel 5 Fiberglass 8 RI														
2 Bras		4 Galvanize		6 Con	crete tile		ABS		۰			used (open			
		ORATION OPE				zed wrapped	3			Saw cu		11	None (o	oen noie)	
	tinuous slot		Mill slot			wrapped				Drilled		Database	01-4		ft.
	vered shutter		Key punched		7 Torc		70			Other (specify)	Bridge			
SCF	KEEN-PERF	ORATED INTERVA		56			. 72				-	- 4.4	'		ft.
	004)/51	D. O. (1) TED (4)	From			. to		ft., Fi				ft. to			£ŧ
	GRAVEL	. PACK INTERVAL	S: From	45	"H	. to	71	ft., Fı ft., Fı			-	- ft. to	- -		ft.
					''	. to						- "			'''
GRO	JT MATER	IIAL: 1 Neat	cement 2 Cem	ent grout	3 1	Bentonite .			4 Other	r Roa	d Sand				
Grout Inte	ervals: Fro	om 0	ft. to 21	1	ft., From		1	ft. to	 -	ft., Fro	om	21	ft. to	45	ft.
What is th	ne nearest	source of possib	ble contamination	n:				10 Livestock	c pens			14 Aba	andoned	water well	
1 Sept	ic tank	4	Lateral lines		7 Pit p	orivy		11 Fuel stora	•			15 Oil	well/Gas	well	
								12 Fertilizer	_			16 Ott	ner (spec	ify below)	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard								13 Insecticio	_	e		None kr		,,	
	_	iiies 0	Occpage pit		0 100	ayara			_		-				
Direction f	rom well?							How m	any fee	et?					
FROM	то		LITHOLOGIC LO)G			FROM	то			PLUG	GING IN	TERVA	LS	
0	2	Topsoil													
2	35	Clay, brown													
35	35.5	Cemented Sa	and												
35.5	45	Sand, fine													
45	62	Sand and gra	vel, fine, medium	, coarse											
62	70	Sand and gra	vel, fine, medium												
70	72	Sand and gra	vel, fine, medium	, coarse											
							18.1	1	1					***	
-							-								
		<u> </u>										***			
		L						1							
			CERTIFICATION: T			(1) const	ructed	(2) recon			3) plugged			risdiction and	
completed				10-20-00		-,,-,						of my kno	wledge	and belief.	Kansas
Water Well	Contractor	r's License No	185		This Wa	iter Well R	ecord v	as complet		no/day/y	Dai	112 h	147	r-00/	
unaer the b	usiness na	ime of Clarke W	/ell & Equipment,	Inc.					by (signa	acure)	···	e "		ン	