


1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ W $\frac{1}{4}$ SE $\frac{1}{4}$ Section Number 17 Township Number T 26 S Range Number R 11 E W
 County: Pratt

Distance and direction from nearest town or city street address of well if located within city?
From Preston KS 1 mile North

2 WATER WELL OWNER: Larry Preisser
 RR#, St. Address, Box #: 105 SE 130th Ave
 City, State, ZIP Code: Cunningham, KS 67035
 Board of Agriculture, Division of Water Resources
 Application Number: 46,178

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1 42 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 42 ft. below land surface measured on mo/day/yr 4-11-06
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 700 gpm. Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 9 Dewatering 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter: 16 in. to 65 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 12 in., weight: 16 lbs./ft. Wall thickness or gauge No. 1/2"
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 65 ft. to 105 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 105 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? None open field
 How many feet? None open field

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	18	Brown clay			
18	23	Sandy tan clay			
23	35	Very Fine to Fine sand			
35	49	Tan + white clay			
49	54	Very Fine to Fine sand			
54	56	Brown clay			
56	104	Fine to coarse sand to medium gravel			
104	105	Tan + yellow clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-11-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 238 This Water Well Record was completed on (mo/day/yr) 4-18-06 under the business name of Premier Pump & Well Service Inc. by signature [Signature]