WATER WELL RE	COKD	FORM W	WC-5	Division of Water Resources App. No.
1 LOCATION OF WA	ATER WELL:	Fraction		Section Number Township No. Range Number
		SW ¼ SW ¼ SW		30 T 26 S R 11 TE VW Global Positioning System (GPS) information:
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				Latitude: .37.747.91(in decimal degrees)
from hearest town of	intersection. If at	Owner's address, encor	Longitude: 098.57326 (in decimal degrees)	
			Elevation: 1867	
				_ <u>Datum</u> : ☐ WGS 84, ☐ NAD 83, <b>②</b> NAD 27
2 WATER WELL OWNER: Philip Dickson			Collection Method:	
RR#, Street Address, Box #: 6 Lakeview Circle			GPS unit (Make/Model: Garmin csx	
City, State, ZIP Code : South F		lutchinson, Ks. 6750	05	☐ Digital Map/Photo, ☑ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☑ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL				
WITH AN "X" IN	1			
SECTION BOX:				
N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr11:			
	Pump test data: Well water wasft. after hours pumping gpn			
		gpm. Well water wasft. after hours pumping gpm		
W         E   Bore Hole Dia				ft., andft.
				er supply    Geothermal    Injection well
SW SE Domestic Feedlot Oil field water supply Dewatering				er supply
Was a chemical/bacteriological sample submitted to Department? Yes V No				
S If yes, mo/day/yr sample was submitted				
1 mile  Water well disinfected? ☑ Yes ☐ No				
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS:  Glued  Clamped  Welded  Threaded				
Casing diameter .5 in. to .80 ft., Diameter in. to ft., Diameter ft.				
			.190	lbs/ft., Wall thickness or gauge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:				
☐ Steel ☐ Stainless Steel				
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)				
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify)				
SCREEN-PERFORATED INTERVALS: From				
From				
GRAVEL PAC	K INTERVALS:			ft., From ft. to ft.
From				
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other				
Grout Intervals: From .20 ft. to .0 ft., From				
What is the nearest source of possible contamination:  ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)				
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well				
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well				
		·	. Distance	from well
FROM TO	LITHOLOG		FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 3 Top se	oil			
3 10 Lt. brn	cly			
	cly & pcs. of ca	liche		
14 25 Lt. brr	cly, f. snd.& pcs			
25 55 Med. 1	to f. snd. & grave	1		
55 65 Lt. gry	. & tn.cly mix f. s			
	/ & f. snd mix 50			
78 100 Med. t	to f. snd. gravel v	v/pcs tn cly		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo/day/year) .1.1:12-09 and this record is true to the best of my knowledge and belief.				
				ecord was completed on (mo/day/year) .11-30-09.
under the business name	of Kosencrant	z-Bomis Lot,		by (signature) Spica Didaca.
				early. Please fill in blanks and check the correct answers. Send three copies ogy Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.
Telephone 785-296-5522. Se	end one copy to WA	TER WELL OWNER and	retain one for	your records. Include fee of \$5.00 for each constructed well. Visit us at
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy				