


1 LOCATION OF WATER WELL: County: Pratt Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 2 Township Number: T 26 S Range Number: R 11 **EW**

Distance and direction from nearest town or city street address of well if located within city?

3 1/2 W OF TURON, KS

2 WATER WELL OWNER: Ocelot Oil Corp. RR#, St. Address, Box #: Suite 117 1 Denver Pl. Durham Board of Agriculture, Division of Water Resources City, State, ZIP Code: Denver, Colo. 80202 Durm # 1 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION: 36 ft. below land surface measured on mo/day/yr 9 July 81

Depth(s) Groundwater Encountered 1. 36 ft. 2. 36 ft. 3. 36 ft.

WELL'S STATIC WATER LEVEL 36 ft. below land surface measured on mo/day/yr 9 July 81

Pump test data: Well water was 100 gpm: Well water was 10 in. to 85 ft. after 85 hours pumping 85 gpm

Est. Yield 100 gpm: Well water was 10 in. to 85 ft. after 85 hours pumping 85 gpm

Bore Hole Diameter 10 in. to 85 ft. and 85 in. to 85 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded
Blank casing diameter 5 in. to 65 ft., Dia. in. to 65 ft., Dia. in. to 65 ft. Threaded
Casing height above land surface 12 in., weight 214 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 65 ft. to 85 ft., From 65 ft. to 85 ft., From 65 ft. to 85 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 85 ft., From 10 ft. to 85 ft., From 10 ft. to 85 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage NONE

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	15	Clay, brown			
15	25	Sand, fine			
25	60	Clay, brown and tan with fine sand			
60	85	Sand, med to coarse and med to coarse gravel, loose			
85	90	Clay, white and tan			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9 July 81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 9 JUN 82 under the business name of Central W ll & Pump I c. Pratt, Ks. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 26
R 11
SEC. 2
SW 1/4 SW 1/4 SW 1/4