

1 LOCATION OF WATER WELL: County: Pratt Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 7 Township Number T 26 S Range Number R 11W E/W

Distance and direction from nearest town or city street address of well if located within city? 3 N of Preston, Kansas

2 WATER WELL OWNER: Merlin Mardis Transpac Drilling RR#, St. Address, Box #: Route 1 1 Main Pl., Suite 600 City, State, ZIP Code: Preston, Ks. 67569 Wichita, Ks. 67202

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section divided into four 9-acre quadrants (NW, NE, SW, SE). The well location is marked with an 'X' in the NW quadrant. A 1-mile scale bar is provided.]

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Unknown. WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on 6/29/82. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield: 60 gpm. Bore Hole Diameter: 8 in. to 80 ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well.

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement. Blank casing diameter: 5 in. to 60 ft., Dia. Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole).

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole).

SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft. GRAVEL PACK INTERVALS: From 10 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 10 ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? East. How many feet? 60.

LITHOLOGIC LOG table with columns FROM, TO, and LITHOLOGIC LOG. Entries: 0-30 Clay, 30-58 Sand and Gravel, 58-63 Clay, 63-80 Sand and Gravel.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 6/29/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186. This Water Well Record was completed on 6/29/82 under the business name of Kellys Water Well Service by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R E/W SEC. 7 1/4 1/4 1/4 1/4