


1 LOCATION OF WATER WELL: County: PRATT Fraction: SW 1/4 NW 1/4 NW 1/4 Section Number: 29 Township Number: T 26 S Range Number: R 11 E

Distance and direction from nearest town or city street address of well if located within city?  
42.0' SOUTH OF 6<sup>th</sup> CENTER LINE & 148.6 EAST OF MAIN ST.; PRESTON, KS

2 WATER WELL OWNER: MORGON TRINKLE  
 RR#, St. Address, Box #: RT 1 BOX 165  
 City, State, ZIP Code: PRESTON, KS 67569  
 Board of Agriculture, Division of Water Resources  
 Application Number: NA

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 2.3 ft. ELEVATION: 1834.34 T.O.C.  
 Depth(s) Groundwater Encountered: 1. 1.19 ft. 2. \_\_\_\_\_ ft. 3. \_\_\_\_\_ ft.  
 WELL'S STATIC WATER LEVEL: 14.57 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Est. Yield \_\_\_\_\_ gpm Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Bore Hole Diameter: 7/8 in. to 23 in. to \_\_\_\_\_ in. to \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW2  
 Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes \_\_\_\_\_ No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  
3 PVC 4 ABS 7 Fiberglass  
 Blank casing diameter: 2 in. to .5 ft. Dia. 2 in. to 2.9 ft. Dia. \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 Casing height above land surface: -6 in., weight \_\_\_\_\_ lbs./ft. Wall thickness or gauge No. 2h 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) \_\_\_\_\_  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) \_\_\_\_\_  
 SCREEN-PERFORATED INTERVALS: From 2.9 ft. to 22.9 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 From \_\_\_\_\_ ft. to \_\_\_\_\_ ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 GRAVEL PACK INTERVALS: From 6.4 ft. to 23.4 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 From \_\_\_\_\_ ft. to \_\_\_\_\_ ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other \_\_\_\_\_  
 Grout Intervals: From 1.0 ft. to 4.4 ft. From 4.4 ft. to 6.4 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? SW How many feet? 290 LIST P.T.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	SAND, black-orange, very fine to fine grained, CLAYEY			
3	10	CLAY, black orange, SANDY, very fine to fine grained. w/ CALICHE at 4			
10	15	CLAY, K. brown, SANDY, fine grained, well sorted, caliche streaks			
15	19	SAND, tan fine to coarse grained, moderately well sorted, subangular to subround, SILTY, wet at 19			
19	23.4	SAND, tan fine to coarse, moderately well sorted, subangular to subround			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-5-94 2-9-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/year) \_\_\_\_\_ under the business name of TBST by (signature) Clay P. [Signature]

OFFICE USE ONLY T 26 R 11 E