

1 LOCATION OF WATER WELL: County: PRATT	Fraction SW 1/4 SW 1/4 NW 1/4	Section Number 33	Township Number T 26 S	Range Number R 12 EW
---	---	-----------------------------	----------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

1 Mile South, 6 Miles West 3/8 Mile South Of Preston, Kans.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	GERALDINE GREEN 1102 Myrtle Pratt, Kans. 67124	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL... 112 ft. ELEVATION:
--	--

1 Mile

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ... **44'** below land surface measured on mo/day/yr ... **April 10 1998**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield ... **700** gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter ... **28 1/4** in. to ... **112** ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
xx2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No **X**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued xx Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
xx2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter ... 16 " in. to ... 72 ' ft., Dia ... in. to ... ft., Dia ... in. to ... ft.			Threaded
Casing height above land surface ... 14 " in., weight ... 16.150 lbs./ft. Wall thickness or gauge No. ... 500			
TYPE OF SCREEN OR PERFORATION MATERIAL:	xx PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	xx 3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From ... 112 ft. to ... 72 ' ft., From ... ft. to ... ft.		
GRAVEL PACK INTERVALS:	From ... ft. to ... ft., From ... ft. to ... ft.		
	From 112 ft. to ... 21 ' ft., From ... ft. to ... ft.		

6 GROUT MATERIAL:	1 Neat cement	xx2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From ... 21 ' ft. to ... 0 ' ft., From ... ft. to ... ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	xx 15 Oil well/Gas well
				12 Fertilizer storage
				16 Other (specify below)
				13 Insecticide storage
Direction from well? SW				How many feet? APP: 1200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	2'	Top Soil.			
2'	15'	Sandy Clay.			
15'	30'	Fine Sand.			
30'	36'	Medium Fine Sand.			
36'	44'	Clay.			
44'	54'	Medium Fine Sand.			
54'	66'	Clay.			
66'	73'	Sandy Clay.			
73'	88'	Course Sand W/Clay Strips.			
88'	100'	Course sand.			
100'	101'	Clay Strip.			
101'	113'	Course Sand & Fine Gravel.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . April 10 1998 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. ... 112 This Water Well Record was completed on (mo/day/yr) . May 21 1998 under the business name of WELLS DRILLING CO. by (signature) <i>Dal Wells</i>

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4