366 12242 Schepmann WATER WELL RECORD	Form WWC-5	Division of Wate	r Resources App. No			
1 LOCATION OF WATER WELL:		Section Number		Range Number		
County: Pratt	l of NE NE	_{/4} 21	Т 26 в 1	R 12 □E XIW		
Street/Rural Address of Well Location;	if unknown, distance & direction	Global Positioning	System (GPS) info	rmation:		
from nearest town or intersection: If at owner's address, check here		Latitude:	Latitude: 37.774674 (in decimal degrees) Longitude: -98.63192 (in decimal degrees) Elevation: Unknown			
Approximately 3 miles north and 5.5 miles east of luka.		Longitude:	Longitude:(in decimal degrees)			
		Elevation:	Elevation: Officiowiii Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: CDM Smith		Collection Method:				
RR#, Street Address, Box #: 345 Riverview - Suite 520		GPS unit (Mak	GPS unit (Make/Model: WAAS			
City, State, ZIP Code : Wichita, KS 67203		Digital Map/Ph	□ Digital Map/Photo, □ Topographic Map, □ Land Survey Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m			
3 LOCATE WELL						
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 98 ft.						
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 06/28/13 ft.						
Pump test data: Well water was not checked ft. after hours pumping gpm -NWNE- EST. YIELD gpm. Well water was ft. after hours pumping gpm						
W -NE- ESI. YIELD gpm. Well water was tt. after nours pumping gpm Bore Hole Diameter 18 in. to 100 ft., and in. to ft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well SWSE ☐ Domestic ☐ Feedlot ☒ Oil field water supply ☐ Dewatering ☐ Other (Specify below)						
Industrial Domestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted 1 mile Water well disinfected? Yes No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Solved Clamped Welded Threaded Casing diameter 10 in to 77 ft Diameter in to ft Diameter in to ft						
Casing diameter 10 in. to 77 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in., Weight 9.03 lbs./ft., Wall thickness or gauge No413						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
l Brance de Maria de Brance de						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From 11 ft. to 91 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 21 ft to 100 ft From ft to ft						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 77 ft. to 97 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 21 ft. to 100 ft., From ft. to ft. From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: Neat ceme	ent Cement grout Bent	onite Other				
6 GROUT MATERIAL: Neat ceme Grout Intervals: From 1 ft. to	21 ft., From	ft. to \overline{ft} .	From	ft. to ft.		
What is the nearest source of possible contamination:						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below) Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well						
Direction from well		e from well	No trail of the Company of the Compa			
FROM TO LITHOLOG	FROM FROM	TO LITHO. L	OG (cont.) <u>or</u> PLU	GGING INTERVALS		
0 4 Topsoil 4 34 Clay, sandy, brown			 	, a mainime managaran da ana ana ana ana ana ana ana ana an		
4 34 Clay, sandy, brown 34 40 Sand, fine to medium				- in in instance		
40 46 Clay, sandy, brown				· · · · · · · · · · · · · · · · · · ·		
46 54 Sand, fine to medium	· · · · · · · · · · · · · · · · · · ·					
54 56 Clay, gray and brown						
56 60 Sand, very fine to fine	>					
60 80 Sand & gravel, fine to						
80 97.5 Sand & gravel, fine to						
97.5 100 Clay, gray and brown				Yearng .		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 06/28/13 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 07/08/13						
under the business name of Clarke Well & Equipment, Inc. by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen PLEASE PRESS FIRMLY and PRINT clearly, Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Department of Health	and Environment, Bureau of Water, G	(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522, Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at				

http://www.kdheks.gov/waterwell/index.html.
KSA 82a-1212