


1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SE 1/4 Section Number 34 Township Number T 26 Range Number R 13

Distance and direction from nearest town or city street address of well if located within city?
 1/2 mile East of Cemetary (Well #2)

2 WATER WELL OWNER: City of Iuka
 RR#, St. Address, Box # : Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Iuka, KS 67066 Application Number: 39786

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 145 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 53' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL .53. ft. below land surface measured on mo/day/yr 1-24-91
 Pump test data: Well water was .59'6" ft. after 20 min. hours pumping .200 gpm
 Est. Yield 1000. gpm: Well water was .59'6" ft. after 8 hours pumping .200 gpm
 Bore Hole Diameter .30 in. to .145 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded
 Blank casing diameter .12-3/4 in. to .110 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface .36 in., weight lbs./ft. Wall thickness or gauge No. .375
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From .110 ft. to .145 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From .106 ft. to .145 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From .106 ft. to 0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southwest How many feet? Approx. 2500'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	4'	Top Soil			
4'	14'	Hard Black Dirt			
14'	47'	Brown Sandy Clay			
47'	60'	Fine to Medium Brown Sand			
60'	80'	Fine Sand w/ Clay Streaks			
80'	127'	Very Fine to Fine Sand			
180'	236'	Very Fine to Fine Sand w/Small Sandstone & Clay Lenses			
236'	249'	Red Bed			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-25-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 514 This Water Well Record was completed on (mo/day/yr) 2-6-91 under the business name of Miller Gearhead & Pump Repair by (signature) Everett Miller

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4