


1] LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SW 1/4 Section Number 26 Township Number T 26 S Range Number R 14 E/W  
 County: PRATT

Distance, and direction from nearest town or city street address of well if located within city?  
2 1/2 S 2 1/2 E OF BYERS Kans

2] WATER WELL OWNER: John Danner #1428  
 RR#, St. Address, Box #: 485 W. RIVER RD. Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: PRATT, Kans. 67124 Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4] DEPTH OF COMPLETED WELL: 86 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 39 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 39 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 8.75 in. to 8 1/2 ft., and in. to ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5] TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 ② PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 7 1/2 ft. Dia. in. to ft. Dia. in. to ft.  
 Casing height above land surface: 24 in. weight lbs./ft. Wall thickness or gauge No. SDR26

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass ⑦ PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped ⑧ Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 7 1/2 ft. to 8 1/2 ft. From ft. to ft.  
 From ft. to ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 30 ft. to 8 1/2 ft. From ft. to ft.  
 From ft. to ft. From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 30 ft. From ft. to ft. From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
CATTLE GRAZING  
 Direction from well? ALL How many feet? 4

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	11	Sandy Clay			
11	13	BR. Clay			
13	22	GREY Clay			
22	39	BR. Clay			
39	51	Sandy Clay			
51	86	GRAVEL			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-8-98 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 12-12-98  
 under the business name of Carl Hays Water Well Serv. by (signature) Carl Hays

OFFICE USE ONLY T R E/W SEC.