


1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ N $\frac{1}{4}$ SE $\frac{1}{4}$ Section Number 30 Township Number T 26 S Range Number R 14 EW (1)
 County: Pratt

Distance and direction from nearest town or city street address of well if located within city?
From Beyers KS, 3 miles South and 1m. to West

2 WATER WELL OWNER: Stan E McAhren
 RR#, St. Address, Box # : 300 Main Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Beyers, KS 67021 Application Number: 25 466

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 180 ft. ELEVATION:



Depth(s) Groundwater Encountered 1 35 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr 4-27-04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 800 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 PVC 4 ABS 7 Fiberglass Welded
 Blank casing diameter 16 in. to 100 ft., Dia 16 in. to ft., Dia in. to ft.

Casing height above land surface 12" in., weight 16 lbs./ft. Wall thickness or guage No. 1/2"
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot Mill slot 4 Key punched 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 7 Torch cut 9 Drilled holes 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 100 ft. to 180 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 180 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 20 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy Soil			
2	24	Fine to Coarse Sand			
24	32	Tan Clay			
32	30	Fine to Coarse Sand to Coarse Gravel			
50	65	Tan Clay			
65	86	Fine to Coarse Sand to Coarse Gravel			
86	100	Tan + White Clay			
100	127	Fine to Coarse Sand to Medium Gravel			
127	137	Brown Clay			
137	144	Fine to Medium Sand to Fine Gravel			
144	155	Brown Clay			
155	180	Very Fine to Coarse Sand to Fine Gravel (Silty)			
180		Brown Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-27-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 238 This Water Well Record was completed on (mo/day/yr) 5-1-04 under the business name of Weninger Irrigation by (signature) Cite/Weininger