


1 LOCATION OF WATER WELL: County: Pratt	Fraction C-S 1/2 1/4 N 1/2 1/4 NE 1/4	Section Number 25	Township Number T 26	Range Number R 14
---	---	-----------------------------	--------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 north, 3/4 west, 990' south of Iuka, Ks.

2 WATER WELL OWNER: FWA Drilling RR#, St. Address, Box #: Box 850980 City, State, ZIP Code: Yukon, Okla. 73085-0980	Board of Agriculture, Division of Water Resources Application Number: McMannis #1
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 33 ft. 2. 33 ft. 3. 33 ft. WELL'S STATIC WATER LEVEL 33 ft. below land surface measured on mo/day/yr Aug. 16, '85 Pump test data: Well water was 33 ft. after 33 hours pumping 33 gpm Est. Yield 80 gpm: Well water was 33 ft. after 33 hours pumping 33 gpm Bore Hole Diameter 10 in. to 100 ft. and 100 in. to 100 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted X No X
--	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) X PVC XX 4 ABS Blank casing diameter 5 in. to 80 ft., Dia 5 in. to 80 ft., Dia 5 in. to 80 ft. Casing height above land surface 12 in., weight 2.34 lbs./ft. Wall thickness or gauge No. 214	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded X
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) X SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped X Saw cut X 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) X	
SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From 80 ft. to 100 ft., From 80 ft. to 100 ft. GRAVEL PACK INTERVALS: From 10 ft. to 100 ft., From 10 ft. to 100 ft., From 10 ft. to 100 ft.	

6 GROUT MATERIAL: 1 Neat cement X Cement grout X 3 Bentonite 4 Other X Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.	What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None
--	--

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Soil, sandy			
2	16	Sand, fine			
16	28	Clay, tan			
28	66	Sand, fine to coarse and fine FM gravel			
66	100	Sand, fine to coarse and fine to coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Aug. 16, '85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) Sept. 16, '85 under the business name of Central Well & Pump, Inc. by (signature) John A. Niemicki INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4