

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Edwards	SE 1/4 SE 1/4 NW 1/4	27	T 26 S	R 16W EW

Distance and direction from nearest town or city street address of well if located within city?

1/2 S, 2 E, 2 S of Trousdale, Kansas

2 WATER WELL OWNER: Norman Wood	Sterling Drilling Co.	Wood H-#1
RR#, St. Address, Box #: Route 1	Box 1006	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Haviland, KS 67059	Pratt, KS 67124	Application Number: 940449

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 157 ft.	ELEVATION: Unknown			
	Depth(s) Groundwater Encountered: 1. 40 ft. 2. . ft. 3. . ft.	WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr 11/15/94			
	Pump test data: Well water was . ft. after . hours pumping . gpm	Est. Yield: 60 gpm: Well water was . ft. after . hours pumping . gpm			
	Bore Hole Diameter: 7. 7/8 in. to 157 ft., and . in. to . ft.	WELL WATER TO BE USED AS:			
	WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well	
	1 Domestic	3 Feedlot	6 Oil field water supply X	9 Dewatering	12 Other (Specify below)
	2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes . No X		If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes . No X			

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X	Clamped .
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded .
2 PVC X	4 ABS	7 Fiberglass		Threaded .
Blank casing diameter: 5 in. to 137 ft., Dia . in. to . ft., Dia . in. to . ft.	Casing height above land surface: 12 in., weight 2.8 lbs./ft.	Wall thickness or gauge No. Sch. 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) .
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut X	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
7 Torch cut	10 Other (specify) .			
SCREEN-PERFORATED INTERVALS: From 137 ft. to 157 ft., From . ft. to . ft.				
GRAVEL PACK INTERVALS: From 20 ft. to 157 ft., From . ft. to . ft.				

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite X	4 Other .
Grout Intervals: From . ft. to . ft., From . ft. to . ft., From . ft. to . ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well X
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage				
Direction from well? South	How many feet? 60			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			157	20	Sand and Gravel
			20	3	Bentonite
			3	0	Top Soil
					Casing cut off 3' below ground level and removed.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 19, 1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 151 This Water Well Record was completed on (mo/day/yr) 12/20/95 under the business name of Sterling Drilling Company by (signature) [Signature]

OFFICE USE ONLY T R EW SEC 1/4 1/4