

MAYHEW A 9-4

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: EDWARDS	SW 1/4 NE 1/4 NW 1/4	4	T 26 S	R 16 E

Distance and direction from nearest town or city street address of well if located within city?

TRUUSDAL 1/4 N EASTSIDE

2 WATER WELL OWNER: STERLING DRILLING CO.	TOM MAYHEW, TRUUSDAL, KS
RR#, St. Address, Box #: 129	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: STERLING, KS 67579	Application Number: T 81-970

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:			
	Depth(s) Groundwater Encountered 1. 43 ft. 2. 55 ft. 3. .ft.			
	WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 12-23-81			
	Pump test data: Well water was .ft. after . hours pumping . gpm			
	Est. Yield . gpm Well water was .ft. after . hours pumping . gpm			
Bore Hole Diameter: 7 7/8 in. to 80 .ft., and . in. to .ft.	WELL WATER TO BE USED AS:			
5 Public water supply	8 Air conditioning	11 Injection well		
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No		

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.				
Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 214				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE: 1/8				12 None used (open hole)
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
7 Torch cut	10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 .ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 50 ft. to 80 .ft., From ft. to ft.				

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: NONE				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	SANDY SOIL			
4	30	SAND			
30	40	CLAY			
40	50	GRAVEL			
50	55	CLAY			
55	80	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-23-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 1-4-82 under the business name of REISER WATER WELL SERV. INC. (signature) <i>Richard Reiser</i>

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 26
R 16
EWD
SEC. 4
SW 1/4 NE 1/4 NW 1/4