

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Edwards		NE 1/4 NE 1/4 NE 1/4		21		T 26 S		R 16 E/W			
Distance and direction from nearest town or city street address of well if located within city?											
2 1/2 miles south, 1 mile east of Trousdale											
2 WATER WELL OWNER: Ron Schultz											
RR#, St. Address, Box # :											
City, State, ZIP Code : Haviland, Kansas 67059											
Board of Agriculture, Division of Water Resources											
Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 60 ft. ELEVATION:									
		Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL ... 10 ft. below land surface measured on mo/day/yr 6/7/90									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield ... 100 gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter. 8 3/4 in. to 60 ft., and in. to ft.									
		WELL WATER TO BE USED AS:									
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted									
		Water Well Disinfected? Yes ☒ No									
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Fiberglass Threaded											
Blank casing diameter ... 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface ... 12 in., weight lbs./ft. Wall thickness or gauge No. SDR-26											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped ☒ 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 25 ft. to 60 ft., From ft. to ft.											
From ft. to ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other											
Grout Intervals: From 2 ft. to 25 ft., From ft. to ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Insecticide storage Livestock											
Direction from well? All How many feet? 4											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		3		Silt & sand							
3		30		Tan clay							
30		60		Sand & gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/7/90 and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 6/20/90											
under the business name of Carl Hayse Water Well Service by (signature) <i>Carl Hayse</i>											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.											