

1 LOCATION OF WATER WELL: County: EDWARDS Fraction: 5 1/4 SW 1/4 SW 1/4 Section Number: 23 Township Number: T 26 S Range Number: R 16 E Distance and direction from nearest town or city street address of well if located within city: TROUSDALE 3 1/2 S 2 1/4 E NORTHSIDE.

2 WATER WELL OWNER: DR. LAUCK OIL CO. INC. RR#, St. Address, Box #: 221 S. BROADWAY SUITE 400 City, State, ZIP Code: WICHITA, KS 67202 Board of Agriculture, Division of Water Resources Application Number: T85-1040

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section (16).]

4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 29 ft. 62 ft. 11-26-85. WELL'S STATIC WATER LEVEL: 22 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 2 ft. after 2 hours pumping. Est. Yield: 389 gpm. Well water was 2 ft. after 2 hours pumping. Bore Hole Diameter: 7 7/8 in. to 75 ft. and 75 in. to 75 ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well. Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes. No.

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below), 2 PVC, 4 ABS, 7 Fiberglass, 8 Concrete tile. CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 55 ft. Dia. Casing height above land surface: 12 in., weight: 2.65 lbs./ft. Wall thickness or gauge No. 21.4. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 7 PVC, 10 Asbestos-cement, 2 Brass, 4 Galvanized steel, 6 Concrete tile, 8 RMP (SR), 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 48 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole), 1 Continuous slot, 3 Mill slot, 6 Wire wrapped, 9 Drilled holes, 2 Louvered shutter, 4 Key punched, 7 Torch cut, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft. GRAVEL PACK INTERVALS: From 45 ft. to 75 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 10 ft. What is the nearest source of possible contamination: NONE. 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage. Direction from well? How many feet?

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-26-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 12-4-85 under the business name of NELSER WATER WELL SERV. INC. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.