

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Edwards		SW 1/4 NW 1/4 NE 1/4	30	T 26 S	R 16 82W

Distance and direction from nearest town or city street address of well if located within city?
 Approx. 3 1/2 miles south and 1 1/2 miles west of Trousdale, KS

2 WATER WELL OWNER: Darrell Wood
 RR#, St. Address, Box #: Route 1
 City, State, ZIP Code: Lewis, KS 67552
 Board of Agriculture, Division of Water Resources
 Application Number: 38,058

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 120 ft.	ELEVATION: unknown
	Depth(s) Groundwater Encountered: 1. 30 ft. 2. ft. 3. ft.	WELL'S STATIC WATER LEVEL: 30 ft. below land surface measured on mo/day/yr 8/17/88
	Pump test data: Well water was not ck. ft. after hours pumping gpm	Est. Yield: 1200 gpm. Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 36 in. to 120 ft., and in. to ft.	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)
 7 Fiberglass
 CASING JOINTS: Glued Clamped Welded X Threaded

Blank casing diameter a) 16 in. to 59 ft., Dia b) 8 5/8 in. to 80 ft., Dia in. to ft.
 Casing height above land surface: 12 in., weight a) 42.05 b) 33.04 lbs./ft. Wall thickness or gauge No a) 2.50 b) 3.75

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) Doerr Bridge Slot

SCREEN-PERFORATED INTERVALS: From 59 ft. to 119 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 119 ft., From ft. to ft.
 Annular Fill From 20 ft. to 25 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage no known source

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Fine sand topsoil			
15	42	Sandy brown clay & fine sand			
42	120	Sand & gravel, fine to med. to coarse			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/17/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 8/26/88 under the business name of Clarke Well & Equipment, Inc. by (signature) *[Signature]*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4