


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: Edwards		Fraction 1/4 c 1/4 ne 1/4	Section number 13	Township number T 26 S R	Range number 17
2. Distance and direction from nearest town or city: 1 1/2 S-2 1/4 W-1/2 S of Trousdale, Ks.			3. Owner of well: Eannith Keen R.R. or street: Fellsburg, Ks. 67048 City, state, zip code:		
4. Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 29 in. Completion date 10-19-77 Well depth 170 ft.	
5. Type and color of material		From	To	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
Sandy top soil		0	3	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Brown clay		3	6	9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft.	
Sand and gravel		6	19	Dia. 16 in. to 170 ft. depth Wall thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 7	
Sandy brown clay		19	26	10. Screen: Manufacturer's name Doerr Type steel Dia. 16 Slot size 3/16 Length 40 Set between 130 ft. and 170 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 3/4-3/8-1/2	
Fine sand		26	29	11. Static water level: 19 ft. below land surface Date 6-30-77 mo./day/yr.	
Dark brown clay & rock		29	37	12. Pumping level below land surfaces: 32 ft. after 1 hrs. pumping 600 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 1400 g.p.m.	
Sand and gravel clean coarse loose		37	70	13. Water sample submitted: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Date 6-30-77 mo./day/yr.	
Sand and gravel little clay		70	73	14. Well head completion: <input type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade	
Sand and gravel clean coarse loose		73	169	15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
Clay		169	170	16. Nearest source of possible contamination: ft. 1500 Direction north Type corral Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
(Use a second sheet if needed)				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name w.l.r. Model number 6-10da 60 Volts 60 Length of drop pipe 80 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation: 2098	19. Remarks: 29772 26 17 13 NAX			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Losencrantz-Bemis 134 Business name Great Bend, Ks. 67538 Address S. Kilgore Signed S. Kilgore Authorized representative X at 6-19-77	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5