

1 LOCATION OF WATER WELL: County: Edwards		Fraction NE ¼ NE ¼ NE ¼		Section Number 20		Township Number T 26 S		Range Number R 17 E (W)																																					
Distance and direction from nearest town or city street address of well if located within city? 1 mile west & 2.5 miles south of Fellsburg, KS																																													
2 WATER WELL OWNER: Mull Farms/Glenn Mull RR#, St. Address, Box # : Rt 1, Box 74 City, State, ZIP Code : Pawnee Rock, KS 67567																																													
Board of Agriculture, Division of Water Resources Application Number:																																													
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 39.5 ft. ELEVATION: 2230.24																																											
		Depth(s) Groundwater Encountered 1 32.53 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 32.80 ft. below land surface measured on mo/day/yr 8-27-03 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-4																																											
		Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																											
		5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Blank casing diameter 2 in. to 39.5 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)																																											
		SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.																																											
SCREEN-PERFORATED INTERVALS: From 39.5 ft. to 24.5 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 39.5 ft. to 23.5 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																													
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 23.5 ft. to 0 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? How many feet?																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3'</td> <td>Silty sand, brown, dry, fine to med grain, few coarse grains</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3'</td> <td>6'</td> <td>Sandy clay, grayish brown to orangish brown, fine to med sand very sl plasticity, small roots, non-staining</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6'</td> <td>16'</td> <td>Sand, tan, sl moist, very fine to med, well sorted</td> <td></td> <td></td> <td></td> </tr> <tr> <td>16'</td> <td>18'</td> <td>Sand, tan, dry, fine to coarse, few very coarse grains, poorly sorted</td> <td></td> <td></td> <td></td> </tr> <tr> <td>18'</td> <td>39.5'</td> <td>Sand, tan, fine to very coarse, rounded to angular gravel</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	3'	Silty sand, brown, dry, fine to med grain, few coarse grains				3'	6'	Sandy clay, grayish brown to orangish brown, fine to med sand very sl plasticity, small roots, non-staining				6'	16'	Sand, tan, sl moist, very fine to med, well sorted				16'	18'	Sand, tan, dry, fine to coarse, few very coarse grains, poorly sorted				18'	39.5'	Sand, tan, fine to very coarse, rounded to angular gravel			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																								
0	3'	Silty sand, brown, dry, fine to med grain, few coarse grains																																											
3'	6'	Sandy clay, grayish brown to orangish brown, fine to med sand very sl plasticity, small roots, non-staining																																											
6'	16'	Sand, tan, sl moist, very fine to med, well sorted																																											
16'	18'	Sand, tan, dry, fine to coarse, few very coarse grains, poorly sorted																																											
18'	39.5'	Sand, tan, fine to very coarse, rounded to angular gravel																																											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-27-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 540 This Water Well Record was completed on (mo/day/yr) 9/23/03 under the business name of Prairie Land Environmental Remediation, Inc. by signature <i>[Signature]</i>																																													