

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Edwards		NE $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$	12	T 26 S	R 18 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approx.  $\frac{1}{2}$  mile south and 1 mile east of Centerview, KS

2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources
Vernon Brown		Application Number: 36,009
RR#, St. Address, Box # : Route 2		
City, State, ZIP Code : Lewis, KS 67552		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 168 ft. ELEVATION: unknown	
		Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft.	
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 5-11-82	
		Pump test data: Well water was not ck'd ft. after hours pumping gpm	
		Est. Yield 800-1000 gpm Well water was ft. after hours pumping gpm	
Bore Hole Diameter 24 in. to 168 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted	
		Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded XX
2 PVC	4 ABS	7 Fiberglass	Threaded

Blank casing diameter 16 in. to 60 ft. Dia 16 in. to 100 ft. Dia in. to ft.

Casing height above land surface 12 in. weight 42.05 lbs./ft. Wall thickness or gauge No. 25.0

TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
		11 Other (specify)	
		12 None used (open hole)	

SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) DOERR BRIDGE SLOT

SCREEN-PERFORATED INTERVALS: From 60 ft. to 68 ft. From ft. to ft.

From 100 ft. to 168 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 168 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 16 Fine sand topsoil &amp; brown clay

16 40 Sand &amp; gravel, med. to coarse

40 44 Brown clay

44 67 Sand &amp; gravel, med. some coarse, clean

67 100 Brown clay w/caliche

100 118 Sand &amp; gravel, fine to med. clean

118 121 Tan clay

121 126 Sand &amp; gravel, fine, clean

126 137 Tan clay w/caliche

137 153 Sand &amp; gravel, fine to med.

153 162 Tan clay

162 164 Sandy green clay w/streak of X

fine sand &amp; gravel

164 168 Sand &amp; gravel, sand, med./fine/clean