LOCATION OF WATER WELL: COUNTY: 024 EDWARDS		NE 1/4 SE				; Township ; T 26				
Distance and direction f 9 1/2 S. 5 E. OF KINSLEY		or city street	address of	well if lo	cated wit	hin city?				
WATER WELL DWNER: RR#, St. Address, Box #		ROLD 103		Boar	d of Agri	culture, Di	vision a	of Water	r Resourc	:es
City, State, ZIP code	: KINSLEY, KS	67547~		Appl	ication N	umber:				
LOCATE WELL'S LOCATION W AN "X" IN SECTION BOX:		DEPTH OF COMPLI Depth(s) Ground			LEVATION: 1.		2.	ft.	3.	ft
\	; ; WE	Pump te	TER LEVEL estdata: We					mo/da ours pu		9.
1 1 1	• •	stimated Yield	gp a: k	dell water	was	ft. after	ho	urs pu	aping .	91
 		ore Hole Diameto	er 8.	. 75 in. to	86 ft	., and	in. to)	ft.	
: : : SW:		ELL WATER TO BE	USED AS: 01	L DOMESTIC						
/	Wa	ns a chemical/b; 'yes, mo/day/yı							isinfecte	ed? Ye
Blank casing diameter Casing height above land	D: 02 PVC 5 in. to surface 12 in	76 ft., Dia ., weight	in.	to ft	., Dia hickness	in. to or gauge No	o f	t.		
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP	D: 02 PVC 5 in. to surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT	in. t lbs/t 86 ft., ft.,	to ft ft. Wall t From From	hickness ft. to ft. to	or gauge No ft. ft.	o f	t.		
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV	D: 02 PVC 5 in. to surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 18 ft. to 18 25 ft. to	in. t lbs/f 86 ft., ft., 86 ft.,	to ft ft. Wall t From From From	hickness ft. to ft. to	or gauge No ft. ft.	o f	t.		
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour	D: 02 PVC 5 in. to surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro Fro ALS: Fro Fro TONITE ft. to 25 cc of possible co	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 18 ft. to 18 ft. to 19 ft. to 25 ft. to	## in. fl	to ft ft. Wall t From From From From	ft. to	or gauge No ft. ft. ft.	ft.		any feet?	
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro ALS: Fro Fro TONITE ft. to 25 ce of possible co	CASING 76 ft., Dia 1., weight 17 PVC 18 SAN CUT 19 76 ft. to 19 ft. to 19 ft. to 19 ft. to 10 ft. to 10 ft. to	## in. fl	ft. Wall t	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.	How m	any feet?	
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL FROM ; TO ; ; 4 ; SILT	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro Fro ALS: Fro Fro ITONITE ft. to 25 ICE of possible co	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 18 ft. to 18 ft. to 19 ft. to 25 ft. to	## in. fl	to ft ft. Wall t From From From From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.		How m		
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL FROM ; TO ; 4 ; SILT 4 ; 21 ; TAN 21 ; 43 ; 05 S	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro Fro ALS: Fro Fro TONITE ft. to 25 CCE of possible co LITHOL & SAND CLAY AND AND 17 SRAVEL	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT The ft. to 18 ft. to 19 ft. to 10 ft. to	## in. fl	ft. Wall t	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.	How m		
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL FROM ; TO ;	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro ALS: Fro Fro TONITE ft. to 25 Ce of possible co LITHOL & SAND CLAY AND AND 17 SRAVEL CLAY	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 19 ft. to 19 ft. to 25 ft. to 26 ft., From 27 ft. to 28 ft. to 29 ft. to 20 ft. CASING 20 ft. to	## in. fl	ft. Wall t	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.	How m)
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL FROM ; TO ;	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro ALS: Fro Fro TONITE ft. to 25 TORITE ce of possible co LITHOL A SAND CLAY AND AND 17 GRAVEL CLAY AND AND 17 GRAVEL	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 19 ft. to 19 ft. to 25 ft. to 26 ft., From 27 ft. to 28 ft. to 29 ft. to 20 ft. CASING 20 ft. to	## in. fl	ft. Wall t	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.	How m		
SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL FROM ; TO ; 4 ; SILT 4 ; 21 ; TAN 21 ; 43 ; 05 S 43 ; 47 ; TAN 47 ; 85 ; 05 S	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro ALS: Fro Fro TONITE ft. to 25 TORITE ce of possible co LITHOL A SAND CLAY AND AND 17 GRAVEL CLAY AND AND 17 GRAVEL	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 19 ft. to 19 ft. to 25 ft. to 26 ft., From 27 ft. to 28 ft. to 29 ft. to 20 ft. CASING 20 ft. to	## in. fl	ft. Wall t	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.	How m		
Blank casing diameter Casing height above land TYPE OF SCREEN OR PERFOR SCREEN OR PERFORATION OP SCREEN PERFORATED INTERV GRAVEL PACK INTERV GROUT MATERIAL 03 BEN Grout Intervals: From What is the nearest sour Direction from well? ALL FROM ; TO ; 4 ; SILT 4 ; 21 ; TAN 21 ; 43 ; 05 S 43 ; 47 ; TAN 47 ; 85 ; 05 S	D: 02 PVC 5 in. to Surface 12 in ATION MATERIAL: 0 ENINGS ARE: 0 Fro ALS: Fro Fro TONITE ft. to 25 TORITE ce of possible co LITHOL A SAND CLAY AND AND 17 GRAVEL CLAY AND AND 17 GRAVEL	CASING 76 ft., Dia 1., weight 17 PVC 18 SAW CUT 19 76 ft. to 19 ft. to 19 ft. to 25 ft. to 26 ft., From 27 ft. to 28 ft. to 29 ft. to 20 ft. CASING 20 ft. to	## in. fl	ft. Wall t	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	ft.	How m		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 10/28/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224

This Water Well Record was completed on (mo/day/yr) 1/09/9 under the business name of CARL HAYSE WATER WELL SVC

by (signature)