USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

)	County	Fraction C	- N	1/2	Section	number	Township number	Range number		
1. Location of well:	Edward	48W74	1/4	-	38.2		т26 s	R 18	₩	
TM. C M d 7 / hand at / an American)					ner of well:		Bill Chadd			
Street address of well location if in city: City, :					r street: state, zip code:		Greensburg, Kansas 67054			
4. Locate with "X" in section below: Sketch map:							6. Bore hole dia. 30 in. Completion date Well depth 144 ft. 5/22/76			
well No. 4 (TH 7- well No. 4 (TH 7- according to his Signs					· · · · · ·		7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary			
							8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock			
							Threaded Welded Surface in. RMP PVC Weight 36.91 lbs./ft.			
1 Mile ────						γ	Dia. 16 in. to 105, depth Wall Thickness: inches or			
5. Type and color of material					From	To	Diain. toft. depth gage No 219 10. Screen: Manufacturer's name			
Top soil					0	2	Metal Prod			
Clay with some sand				2	30	Slot/gauze 1/8" Set between 8/	Length 40 ft. and 101			
Med. to coarse sand & gravel				30	69	Gravel back? <u>VC</u> Size ran		172		
Clay					69	80	11. Static water level: 25 ft. below land sur	face Date 3/25	day/yr.	
Med. to coarse sand & gravel				80	102	12. Pumping level below land	surfaces: No TE	s /		
Clay					102	124	ft. after h	rs. pumping	g.p.m.	
Med. to coarse sand & gravel					124	144	٠	mo./	g.p.m. day/yr.	
Clay					144	150	14. Well head completion:) ate		
								Z Inches above gr	rade	
							15. Well grouted?	Bentonite K Co	oncrete	
		••••••••••••••••••••••••••••••••••••••					16. Negrest source of possible ft. 4500 Direction			
							Well disinfected upon comple	rion?Yes	× No L	
						17. Pump: Manufacturer's name	Not installed	*%		
						Model number 22.814 Length of drop pipe 80	HP <u>80</u> Volts ft. capacity 200 g			
						Type: Submersible	X Turbine			
(Use a second sheet if needed)						Jet Centrifugal	Reciproce	ating S		
,	19. Remarks:				-	_	20. Water well contractor's c This well was drilled under my	ertification:	, 60	
√ Z(95′ Topography:							is true to the best of my knowl	edge and belief.	(4	
— НіІІ						Layne Western Co. 102 Business name Wichta Kansas			se No.	
Slope Upland Valley							Signed Authorized repr	R Dat 7/	13/2 SI	